

PRIMARY CORNER DESCRIPTION Sec. Cor. for 28, 29, 32 and 33

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by W.H. Byars, Deputy Surveyor under contract # 448 dated June 13, 1882 (DCSO records Vol. 19 Page(s) 8062-63)

Set a Laurel post 4 ft. long, 4" sq., 22" in the ground mkd. T31S R7W S28 on NE. face; S33 on SE. face; S32 on SW. face; and S29 on NW. face; also one notch on S. and 4 notches on E. angles of same, for the cor. to secs. 28, 29, 32 and 33, from which

- A Pine 32" dia., bears N.74°E., 163 lks. dist. mkd. T31S R7W S28 BT.
- A Pine 32" dia., bears S.58°E., 184 lks. dist. mkd. T31S R7W S33 BT.
- A Laurel 16" dia., bears S.60°W., 46 lks. dist. mkd. T31S R7W S32 BT.
- A Pine 28" dia., bears N.65°W., 203 lks. dist. mkd. T31S R7W S29 BT.

BLM resurvey by Donald Beck, Cadastral Surveyor, under Group #531 - Surveyed Oct 1963/June 1964 - (DCSO records Vol. 33 Page(s) 13637)

Point for the sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28" long, 2 1/2" dia., 22" in the ground, with brass cap mkd:

T 31 S R 7 W
S 29 S 28
S 32 S 33
1963

from which

- A Fir 24" dia., bears N.83°E., 53 lks. dist. mkd. T31S R7W S28 BT.
- A Cedar 32" dia., bears S.71°E., 67 lks. dist. mkd. T31S R7W S33 BT.
- A Fir 15" dia., bears S.80°W., 130 lks. dist. mkd. T31S R7W S32 BT.
- A Fir 20" dia., bears N.30°W., 46 lks. dist. mkd. T31S R7W S29 BT.