

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 28 and 29

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by W.H. Byars, Deputy Surveyor under contract # 448 dated June 13, 1882 (DCSO records Vol. 19 Page(s) 8064)

Set a Pine post, 3 ft. long, 4" sq., 18" in the ground, mkd. 1/4 S. on W. side for the 1/4 sec. cor., from which
A Pine 42" dia., bears S.29°E., 168 lks. dist. mkd. 1/4 S BT
A Pine 30" dia., bears S.84°W., 159 lks. dist. mkd. 1/4 S BT

BLM resurvey by Donald Beck, Cadastral Surveyor, under Group #531 - Surveyed Oct 1963/June 1964 - (DCSO records Vol. 33 Page(s) 13638-39)

The 1/4 sec. cor., determined at record distance from the remains of the original bearing trees:

A Pine 55" dia., bears S.29°E., 168 lks. dist., no marks visible on bark blaze.

A Pine snag 33" dia., bears N.89°W., 159 lks. dist. mkd. 1/4 S on open blaze. (Rec. brg. S.84°W.)

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

1/4
S 29 S 28
T 31 S R 7 W
1963

from which new bearing trees:

A Fir 11" dia., bears S.87 1/2°E., 38 lks. dist. mkd. 1/4 S28 BT.

A Fir 14" dia., bears N.35 1/2°W., 48 1/2 lks. dist. mkd. 1/4 S29 BT.