

PRIMARY CORNER DESCRIPTION Sec. Cor. for 20, 21, 28 and 29

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by W.H. Byars, Deputy Surveyor under contract # 448 dated June 13, 1882 (DCSO records Vol. 19 Page(s) 8064)

-
- Set a Cedar post, 4 ft. long, 4" sq., 18" in the ground, mkd. T31S R7W S21 on NE. face; S28 on SE. face; S29 on SW. face; and S20 on NW. face. Also 2 notches on S. and 4 on E. angles of same, for the cor. to secs. 20, 21, 28 and 29, from which
- A Sugar Pine 60" dia., bears N.10°E., 18 lks. mkd. T31S R7W S21 BT.
 - A Pine 24" dia., bears S.5°E., 29 lks. dist. mkd. T31S R7W S28 BT.
 - A Laurel 14" dia., bears S.40°W., 67 lks. dist. mkd. T31S R7W S29 BT.
 - A Cedar 22" dia., bears N.57°W., 8 lks. dist. mkd. T31S R7W S20 BT.

BLM resurvey by Donald Beck, Cadastral Surveyor, under Group #531 - Surveyed Oct 1963/June 1964 - (DCSO records Vol. 33 Page(s) 13639)

-
- The Sec. cor., determined at record bearing and distance from the remains of the original bearing trees:
- A Pine snag 60" dia., bears N.10°E., 18 lks. dist., no marks visible.
 - A stump hole bears S.5°E., 29 lks. dist.
 - A Cedar 30" dia., bears N.57°W., 8 lks. dist. mkd. with old axe marks on open, burned blaze.

At the corner point
Set an iron post, 28" long, 2 1/2" dia., 22" in the ground, with brass cap mkd:

T 31 S R 7 W
<u>S 20 S 21</u>
S 29 S 28
1963

- from which new bearing trees:
- A Fir 10" dia., bears N.38 3/4°E., 66 lks. dist. mkd. T31S R7W S21 BT.
 - A Fir 6" dia., bears S.5°E., 53 lks. dist. mkd. T31S R7W S28 BT.
 - A Fir 15" dia., bears S.16½°W., 53 lks. dist. mkd. T31S R7W S29 BT.
 - A Fir 9" dia., bears N.35 3/4°W., 50 lks. dist. mkd. T31S R7W S20 BT.

Fd. ok by Jerry Estabrook 4/2003 - C.S. File 65/45-19