

TOWNSHIP 31 RANGE 07 POINT IDENTIFIER # 300400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 16, 17, 20 and 21

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 448 dated June 13, 1882 (DCSO records Vol. 19 Page(s) 8066)

Set a Fir post 4 ft. long, 4' sq., 20" in the ground marked T31S R7W S16 on NE. face; S21 on SE. face; S20 on SW. face; and S17 on NW. face. Also, 3 notches on S. and 4 on E. angles of same for the cor. to secs. 16, 17, 20 and 21, from which

- A Pine 12" dia., bears N.72°E., 15 lks. dist. mkd. T31S R7W S16 BT.
- A Fir 7" dia., bears S.78°E., 11 lks. dist. mkd. T31S R7W S21 BT.
- A Fir 38" dia., bears S.25°W., 29 lks. dist. mkd. T31S R7W S20 BT.
- A Laurel 7" dia., bears N.55°W., 54 lks. dist. mkd. T31S R7W S17 BT.

Douglas Co. Surveyors Office - V.R. Tracy; M. Darby; J. Barnett, crew - April 16, 1965 - C.S. File 54/3-2

Found - Orig. 38" now 42" Fir S.25°w., 19.1 ft., shows "T3S" on old bark scribe. This BT now snag, approx. 60 ft. high.

All other BTs gone.

Set Brass cap at cor. mkd: County Surveyors Office

T 31 S R 7 W
S 17 | S 16
S 20 | S 21
1965

Corner point falls on 14" log, Set brass cap under log.

- New BTs- 14" D.Fir N.10°W., 34.0 ft. mkd. T31S R7W S17 CSBT
- 26" D.Fir N.70°E., 37.6 ft. mkd. T31S R7W S16 CSBT
- 24" D.Fir S.33°E., 43.6 ft. mkd. T31S R7W S21 CSBT
- 26" D.Fir S.46°W., 51.7 ft. mkd. T31S R7W S20 CSBT

This corner lies in small ravine sloping N.40°E.