

TOWNSHIP 31 RANGE 07 POINT IDENTIFIER # 300500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 8, 9, 16 and 17

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 448 dated June 13, 1882 (DCSO records Vol. 19 Page(s) 8067-68)

Set a Fir post 4 ft. long, 4" sq., 18" in the ground mkd. T31S R7W S9 on NE.; S16 on SE.; S17 on SW.; and S8 on NW. Also, 4 notches on S. and E. angles for the cor. to secs. 8, 9, 16 and 17, from which

A Fir 10" dia., bears N.62°E., 21 lks. dist. mkd. T31S R7W S9 BT.

A Laurel 12" dia., bears S.32°E., 31 lks. dist. mkd. T31S R7W S16 BT.

A Laurel 5" dia., bears S.24°W., 47 lks. dist. mkd. T31S R7W S17 BT.

A Laurel 7" dia., bears N.37°W., 45 lks. dist. mkd. T31S R7W S8 BT.

Survey by Howard W. Johnstone, LS #498 - For: Roseburg Lumber Co. - Dec. 20, 1982 - M 90-34

Set 5/8" x 36" iron rod and alum. cap mkd. with "LS 498", from which BTs:

16" Fir N.44°E., 26.8 ft.

15" Fir S.29°E., 30.0 ft.

12" Fir S.56°W., 26.3 ft.

20" Fir N.28°W., 31.0 ft.