

TOWNSHIP 31 RANGE 07 POINT IDENTIFIER # 300640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 4 and 5

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor, under Contract #152, dated June 3, 1871, - (DCSO records Vol. 19 Page(s) 8021)

Set ¼ sec. post, from which
A Laurel 8" dia., bears S.25°E., 92 lks.
A Pine 20" dia., bears N.70°W., 142 lks.

GLO survey by Gerald A. Sorrels, U.S. Surveyor, under under Special Instructions dated March 1, 1917 - (DCSO records Vol. 19 Page(s) 8091-92) and duplicated info. in Vol. 27 Pg. 11637

Point for the old ¼ sec. cor., located by reference to the bearing trees. At the exact cor. point
Set an iron post, 3 ft. long, 1" dia., 26" in the ground, for ¼ sec. cor., with brass cap mkd: ¼
S 5 | S 4
1918

from which
A Fir 7" dia., bears S.5°E., 43 lks. dist. mkd. ¼ S4 BT.
(New BT)
A Madrona 10" dia., bears S.14°E., 14 lks. dist. mkd. ¼ S4 BT.
(Old BT)
A Yellow Pine 24" dia., bears N.71°15'W., 142 lks. dist. mkd. ¼ S5 BT. (New BT)

Douglas Co. Surveyors Office - Vernon "Ray" Tracy, Mike Darby, Terry Connell, crew - May 17, 1965 - C.S. File 54/3-3

Found - 1918 GLO brass cap mkd. "¼ S5 | S4 1918".
7" now 12" Fir S.5°E., 28.4 ft., down. Open and find "B" scribe.
24" now 18" Y.Pine N.71¼°W., 93.7 ft., down and badly rotted, shows "¼S" scribe.
No trace orig. Madrone tree.
New BTs -21" D.Fir S.21°W., 29.4 ft. mkd. ¼ S5 CS BT.
7" D.Fir S.84°E., 64.8 ft. mkd. ¼ S4 CS BT.
This corner lies 10.0 ft. West of dry ravine, course SE.

Fd. OK, Feb. 6, 1981 by H. Johnstone - M 86-62
Fd. OK by Kris DeGroot - July 2007 - M153-58