

TOWNSHIP 31 RANGE 07 POINT IDENTIFIER # 304700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 32 & 33 only, T30-7

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Gerald A. Sorrels, U.S. Surveyor, under Group #36, surveyed March/April 1918 - (DCSO records Vol. 17 Page(s) 7293-94) and duplicate info. in Vol. 27 Pg. 11616)

Set an Iron post, 3 ft. long, 2" dia., 24" in the ground, for cor. of secs. 32 and 33, with brass cap mkd.

T 30 S	R 7 W
S 32	S 33

1918

from which
A W.Oak 6" dia., bears N.87°E., 197 lks. dist. mkd. T30S R7W S33 BT.
A Yellow Pine 30" dia., bears N.59°W., 114 lks. dist. mkd. T30S R7W S32 BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy, Mike Darby; Terry Connell, crew - July 1965 - C.S. File 53/40-81

Found - 1918 GLO brass cap in mound of stone.
Orig. 6" now 7" W.Oak N.87°E., 130.0 ft., rotted, no scribe found.
Orig. 30" now 30" Pine N.59°W., 75.2 ft., now snag, shows "T30SR7W S32 BT"
New BT - 10" B.Oak N.25°E., 128.6 ft. mkd. T30S R7W S33 CSBT.
This corner lies on top of bluffs approx. 250 ft. East of W.C. to secs. 4 & 5, T31-7.

Survey by Howard Johnstone, LS #498 - For: Roseburg Lumber Co. - Sept. 24, 1984 - M 97-50

Found - Mound of stones but no brass cap and iron pipe.
30" Pine N.59°W., 75.2 ft., snag.
6" Oak N.87°E., 130.0 ft., rotted.
10" Oak N.25°E., 128.6 ft., good.
Set 5/8" x 18" Iron rod and alum. cap in stone mound. Cap mkd. "LS 498".