

TOWNSHIP 31 RANGE 07 POINT IDENTIFIER # 340200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 28 and 33

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by W.H. Byars, Deputy Surveyor under contract # 448 dated June 13, 1882 (DCSO records Vol. 19 Page(s) 8063)

-----  
Set a Laurel post 40" long, 4" sq., 18" in the ground, marked 1/4 S. on N. side for the 1/4 sec. cor., from which

A Fir 20" dia., bears N.62°E., 53 lks. dist. mkd. 1/4 S BT.

A Fir 18" dia., bears S.31°W., 40 lks. dist. mkd. 1/4 S BT.

BLM resurvey by Donald Beck, Cadastral Surveyor, under Group #531 - Surveyed Oct 1963/June 1964 - (DCSO records Vol. 33 Page(s) 13637-38)

-----  
The 1/4 sec. cor., determined at record bearing and distance from the original bearing trees:

A Fir 48" dia., bears N.62°E., 56 lks. dist., (53 lks. to face), mkd. 1/4 S BT on bark blaze. (Rec. dist. 53 lks.)

A Fir 33" dia., bears S.31°W., 42 lks. dist. (40 lks. to face) mkd. 1/4 S BT on bark blaze. (Rec. dist. 40 lks.)

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 22" in the ground, with brass cap mkd:

1/4 S 28  
S 33

T 31 S R 7 W  
1963