

TOWNSHIP 31 RANGE 07 POINT IDENTIFIER # 340500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 9 and 16

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by W.H. Byars, Deputy Surveyor under contract # 448 dated June 13, 1882 (DCSO records Vol. 19 Page(s) 8068)

-----  
Set a Fir post 4 ft. long, 4" sq., 18" in the ground mkd. 1/4 S. on N. side for the 1/4 sec. cor., from which  
A Fir 26" dia., bears S.36°E., 9 lks. dist. mkd. 1/4 S BT.  
A Fir 16" dia., bears N.52°E., 6 lks. dist. mkd. 1/4 S BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & C. Stone, crew - Nov. 1966 - C.S. File 54/36-4

-----  
Found - 26" now 40" D.Fir S.36°E., 5.9 ft., faint bark scribe "1/4S".

No trace of 16" D.Fir N.52°E., 4.0 ft.

Find a Fir N.1°E., 8.8 ft., no scribe visible.

Set Brass cap at cor. mkd: County Surveyors Office

T 31 S R 7 W

1/4  $\frac{S \quad 9}{S \quad 16}$

1966

New BTs- 26" D.Fir N.1°E., 8.8 ft. mkd. 1/4 S9 CS BT.

11" Laurel S.4°E., 22.9 ft. mkd. 1/4 S16 CS BT.

This corner lies South of ravine, 25.0 ft. and West of ravine on small spur, running SE. and NW.

Fd. and used in BLM resurvey by Owen C. Chatters II, Cadastral Surveyor, under Group #834, surveyed April/June 1974 - (DCSO records Vol. 39 Page(s) 15746)