TOWNSHIP 31 RANGE 07 POINT IDENTIFIER # 340600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 4 and 9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor, under Contract #152, dated June 3, 1871, - (DCSO records Vol. 19 Page(s) 8021)

Set ¼ sec. post, from which
A Pine 30" dia., bears N.75°E., 102 lks.
A Pine 20" dia., bears S.75°W., 131 lks.

GLO survey by Gerald A. Sorrels, U.S. Surveyor, under under Special Instructions dated March 1, 1917 - (DCSO records Vol. 19 Page(s) 8087) and duplicated info. in Vol. 27 Pg. 11634

The old ¼ sec. cor., located by reference to the bearing trees. At the exact cor. point
Set an iron post 3 ft. long, 1" dia., 26" in the ground, for ¼ sec. cor., with bears cap mkd. ¼ S 4 / S 9 / 1918

from which
A Yellow Pine 36" dia., bears N.76°30'E., 105 lks. dist. mkd. ¼ S4 BT. (Old BT)
A Yellow Pine 24" dia., bears S.78°W., 133 lks. dist. mkd. ¼ S9 BT (Old BT)

Douglas County Surveyors Office - John M. Powell, Frank Jones, C. Stone, crew - Nov. 1966 - C.S. File 54/36-2

Found - 1918 Brass cap, properly marked. (GLO)
36" Yellow Pine now 40", N.76½°E., 69.3 ft., scribe visible "¼ BT".
24" Yellow Pine, now down and burned, S.78°W., 87.8 ft.
New BT - 27" Pine S.33½°E., 61.4 ft. mkd. ¼ S9 CS BT.

Fd. OK, Feb. 6, 1981 by H.Johnstone - M 86-62