

TOWNSHIP 31 RANGE 07 POINT IDENTIFIER # 340700

PRIMARY CORNER DESCRIPTION No. 1/4 Cor. for Sec. 4 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Gerald A. Sorrels, U.S. Surveyor, under Group #36, surveyed March/April 1918 - (DCSO records Vol. 17 Page(s) 7293) and duplicate info. in Vol. 27 Pg. 11616)

Set an iron post, 3 ft. long, 1" dia., 26" in the ground, for 1/4 sec. cor. of sec. 4 only, with brass cap mkd.

1/4 S 4
1918

from which

A Cedar 16" dia., bears S.70°E., 28 lks. dist. mkd. 1/4 S4 BT.

A Yellow Pine 7" dia., bears S.66°30'W., 70 lks. dist. mkd. 1/4 S4 BT.

Mark Smalley - For: Roseburg Resources Co. - January 2000 - M 134-7

Found - 1918 GLO brass cap on iron pipe.

17" Pine S.66½°W., 46.2 ft. healed. Orig.

21" Cedar S.70°E., 18.5 ft. snag healed. Orig.

Scribed- 20" Pine N.28°W., 9.1 ft. "1/4 S BT"

14" Pine N.2°W., 37.2 ft. "1/4 S BT"

20" Pine N.29°E., 28.6 ft. "1/4 S BT"