

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 33 only, T30-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars, Deputy Surveyor, under Contract #152, dated June 3, 1871, - (DCSO records Vol. 17 Page(s) 7230)

-----

Set ¼ sec. post, from which  
A Pine 16" dia., bears N.25°E., 20 lks. dist.  
A Pine 12" dia., bears S.78°E., 46 lks. dist.

GLO survey by Gerald A. Sorrels, U.S. Surveyor, under Special Instructions, Group #36, surveyed March/April 1918 - (DCSO records Vol. 17 Page(s) 7292-93) and duplicate info. Vol. 27 Pg. 11615)

-----

The old ¼ sec. cor., which is a badly decayed post, witnessed as described by the surveyor general. Alongside the old cor. Set an Iron post 3 ft. long, 1" dia., 26" in the ground, for ¼ sec. cor. of sec. 33 only, with brass cap mkd:  $\frac{1}{4}$  S 33  
1918

from which  
A Yellow Pine 24" dia., bears N.25°E., 22 lks. dist. mkd.  $\frac{1}{4}$  S33 BT.  
A Fir 5" dia., bears N.44°30'W., 25 lks. dist. mkd.  $\frac{1}{4}$  S33 BT.

Douglas Co. Surveyors Office - Vernon R. Tracy; Mike Darby; Jack Barnett, crew - March 1965 - C.S. File 53/40-63

-----

Found - 1918 Brass cap mkd. " $\frac{1}{4}$  S33 1918".  
24" now 28" Yellow Pine N.25°E., 14.5 ft., face burned, shows scribe.  
5" rotted stump, N.44½°W., 16.5 ft., trace of reverse scribe, possibly the "B".  
New BTs -10" Pine N.12°W., 40.4 ft. mkd.  $\frac{1}{4}$  S33 CS BT.  
26" Pine N.74°E., 33.7 ft. mkd.  $\frac{1}{4}$  S33 CS BT.  
This corner lies approx. 100 ft. West of small creek, flowing NW.

Mark Smalley - For: Roseburg Resources Co. - January 2000 - M 134-7

-----

Found - 1918 GLO brass cap on iron pipe.  
25" (26") Pine N.74°E. 33.7 ft. scribe visible snag.  
10" (12") Pine N.12°W., 40.4 ft. scribe visible.  
28" (35") Pine N.25°E., 14.5 ft. open face. orig.  
Scribed- 18" Fir N.56°E., 32.2 ft. " $\frac{1}{4}$  S BT"  
13" Pine S.43°E., 34.2 ft. " $\frac{1}{4}$  S BT"

continued next page

TOWNSHIP 31 RANGE 07 POINT IDENTIFIER # 342700

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 33 only, T30-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Ron Quimby - Crew: R. Olsen & J. Leonard - 9/2017 - C.S. File 65/99-3

-----

Found - 1918 GLO brass cap on iron pipe (properly mkd)  
20" Fir N.56°E., 32.2 ft. vis. scar.  
14" Pine S.43°E., 34.2 ft. faint scribes  
Other BTs of record are burnt out.  
New - 14" Pine S.27°W., 55.5 ft. scribed ¼ S33 BT.  
18" Pine N.37°W., 53.1 ft. scribed ¼ S33 BT.  
Note - Area badly burnt 8/2017  
Dec. 15½°E.