

TOWNSHIP 31 RANGE 07 POINT IDENTIFIER # 400100

PRIMARY CORNER DESCRIPTION Sec. Cor. for 33 & 34; 3 & 4 of T32-7

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by W.H. Byars, Deputy Surveyor under contract # 420 survey dated Sept 16, 1881 (DCSO records Vol. 19 Page(s) 8026)

Set a Cedar post, 4½ ft. long, 4" sq., 20" in the ground, for the cor. to secs. 3, 4, 33 and 34, marked T31S R7W S34 on NE. face; T32S S3 on SE. face; S4 on SW. face; and S33 on NW face; also three notches on E. and W. angles of same, from which

- A Cedar 14" dia., bears N.50°E., 25 lks. mkd. T31S R7W S34 BT.
- A Chinquapin 12" dia., bears S.36°E., 68 lks. mkd. T32S R7W S3 BT.
- A Sugar Pine 28" dia., bears S.20°W., 17 lks. mkd. T32S R7W S4 BT.
- A Fir 18" dia., bears N.32°W., 30 lks. mkd. T32S R7W S33 BT.

Cor. Fd. and used in Byars GL0 survey of 1882. (DCSO records, Vol. 19 Page 8054)

BLM resurvey by Donald Beck, Cadastral Surveyor, under Group #531, surveyed Oct. 1963\June 1964 (DCSO records Vol. 33 Page(s) 13620)

The Sec. cor., determined at record bearing and distance from the remains of the original NE bearing tree:

- A Cedar snag 20" dia., bears N.50°E., 25 lks. dist, mkd. S and other illegible scribe marks on open blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. dia., 23 ins. in the ground, with brass cap marked

T 31 S R 7 W
S 33 | S 34
S 4 | S 3
T 32 S R 7 W
1964

from which new bearing trees

- A Fir 28" dia., bears N.17 3/4°E., 60 lks. dist.,mkd. T31S R7W S34 BT.
- A Fir 23" dia., bears S.59 3/4°E., 75 lks. dist., mkd. T32S R7W S3 BT.
- A Fir 7" dia., bears S.59°W., 82 lks. dist., mkd. T32S R7W S4 BT.
- A Cedar 15" dia., bears N.77¼°W., 109 lks. dist., mkd. T31S R7W S33 BT.

(Cont. Next Page)

TOWNSHIP 31 RANGE 07 POINT IDENTIFIER # 400100

PRIMARY CORNER DESCRIPTION Sec. Cor. for 33 & 34; 3 & 4 of T32-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Survey by Kristian DeGroot, L.S. #1941 - For: Allen & Gibbons Logging - Nov. 28, 1983 - C.S. File 58/229-21

Found - 1964 BLM brass cap properly marked, projecting 4" above ground.

Orig. 20" rotted and uprooted Cedar snag, its root hole bears N.50°E., 16.5 ft.

1964 BT, a 30" D.Fir bears N.17 3/4°E., 39.6 ft. with a healed blaze.

1964 BT, a 26" D.Fir bears S.59 3/4°E., 49.5 ft. with a healed blaze.

1964 BT, a 10" uprooted D.Fir snag, its root hole bears S.59°W., 54.1 ft.

New BTs - 20" I.Cedar bears S.82½°W., 60.4 ft. scribed "T32S R7W S4 BT" with a brass washer "LS 1941" nailed into lower blaze.

8" Chinquapin bears N.15°W., 47.6 ft. scribed "T31S R7W S33 BT" with a brass washer "LS 1941" nailed into lower blaze.

Distances to new BTs are measured to a nail in the root crown at the side and center of the tree. I painted 6" red bands around new BTs and all bearing tree faces red and attached BT tags.

Fd. BC & accessories by G Neitsch, 11/2022 - M181-49