

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 33 and 34

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by W.H. Byars, Deputy Surveyor under contract # 448 dated June 13, 1882 (DCSO records Vol. 19 Page(s) 8054-55)

Set a Laurel post 40" long, 3" sq., 20" in the ground marked 1/4 S. on W. side for the 1/4 sec. cor., from which
A Fir 34" dia., bears N.42°E., 36 lks. dist. mkd. 1/4 S BT.
A Fir 32" dia., bears N.70°W., 19 lks. dist. mkd. 1/4 S BT.

BLM resurvey by Donald Beck, Cadastral Surveyor, under Group #531 - Surveyed Oct 1963/June 1964 - (DCSO records Vol. 33 Page(s) 13629)

The 1/4 sec. cor., determined at record bearing and distance from the remains of the original bearing trees:

- A Fir snag 38" dia., bears N.42°E., 36 lks. dist. mkd. 1/4 S on bark blaze.
- A Fir 45" dia., bears N.70°W., 19 lks. dist., with no marks visible.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 22" in the ground, with brass cap mkd:

T 31 S R 7 W
1/4
S 33 S 34
1964

from which new bearing trees:

- A Fir 8" dia., bears S.81 1/2°E., 36 lks. dist. mkd. 1/4 S34 BT
- A Fir 8" dia., bears S.13 1/4°W., 41 1/2 lks. dist. mkd. 1/4 S33 BT.

Douglas Co. Surveyors Office - Randall Smith, Stephen Flause; Sept. 16, 1996 - C.S. File 65/9-15

Found - 3 1/4" dia. brass cap on an iron pipe is found 6" below ground. (1964 BLM)

Accessories Found -

32" now 45" dia. down D.Fir, large root hole at record "N.70°W., 12.5 ft." O.B.T.

Orig. NE BT now gone.

8" now 11" dia. 1 ft. high rotted D.Fir stump, scribing found "BT" bears S.81 1/2°E., 23.8 ft. (agrees with rec.) 1964 BLM

8" now 14" dia. D.Fir with a fully healed single blaze, bears S.13 1/2°W., 27.4 ft. (agrees with rec.) 1964 BLM

New Accessories -

5" dia. D.Fir, double blazed and scribed "1/4 S34 CS BT" bears S.89°E., 46.8 ft.

(Cont. Next Page)

TOWNSHIP 31 RANGE 07 POINT IDENTIFIER # 400140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 33 and 34

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

New Accessories continued -
6" dia. D.Fir, double blazed and scribed "¼ S33 CS BT"
bears S.52°W., 26.1 ft.
19" dia. Madrone, double blazed and scribed "¼ S33 CS BT"
bears N.29½°W., 30.7 ft.