

PRIMARY CORNER DESCRIPTION Sec. Cor. for 21, 22, 27 and 28

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 448 dated June 13, 1882 (DCSO records Vol. 31 Page(s) 8056-57)

Set Fir post 4" sq., 4 ft. long, 20" in the ground, mkd. T31S R7W S22 on NE. face; S27 on SE. face; S28 on SW. face; and S21 on NW. face. Also 2 notches on S. and 3 on E. angles of same, from which
A Chinquapin 10" dia., bears N.12°E., 23 lks. dist. mkd. T31S R7W S22 BT.
A Pine 46" dia., bears S.42°E., 63 lks. dist. mkd. T31S R7W S27 BT.
A Laurel 7" dia., bears S.33°W., 25 lks. dist. mkd. T31S R7W S28 BT.
A Laurel 12" dia., bears N.60°W., 82 lks. dist. mkd. T31S R7W S21 BT.

BLM resurvey by Donald Beck, Cadastral Surveyor, under Group #531 - Surveyed Oct 1963/June 1964 - (DCSO records Vol. 33 Page(s) 13632-33)

Point for the sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28" long, 2 1/2" dia., 25" in the ground, with brass cap mkd:
T 31 S R 7 W
S 21 S 22
S 28 S 27
1964

from which
A Fir 9" dia., bears N.59°E., 23 lks. dist. mkd. T31S R7W S22 BT.
A Fir 15" dia., bears S.76°E., 200 lks. dist. mkd. T31S R7W S27 BT.
A Fir 15" dia., bears S.18½°W., 214 lks. dist. mkd. T31S R7W S28 BT.
A Fir 15" dia., bears N.81°W., 29 lks. dist. mkd. T31S R7W S21 BT.

Douglas Co. Surveyors Office - Randall Smith, Stephen Flause, Sept. 12, 1996 - C.S. File 65/9-13

Found - 3¼" dia. brass cap on a 2½" O.D. iron pipe, protrudes 6" above ground. (1964 BLM)
Accessories Found -
9" now 11" dia. 1 ft. high D.Fir stump. Open and find scribing "BT" bears N.59°E., 14.7 ft. (rec. N.59°E., 15.2 ft.) 1964.

(Cont. Next Page)

TOWNSHIP 31 RANGE 07 POINT IDENTIFIER # 400300

PRIMARY CORNER DESCRIPTION Sec. Cor. For 21, 22, 27 and 28

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Accessories Found continued -

15" now 23" dia. D.Fir with a fully healed blaze bears N.81°W., 19.1 ft. (agrees with rec.) 1964

15" now 16" dia. 1 ft. high D.Fir stump, with a fully healed lower blaze, bears S.18½°W., 141.2 ft. (agrees with rec.) 1964 BLM

1964 SE BT not found

New Accessories -

6" dia. D.Fir, double blazed and scribed "T31S R7W S28 CS BT" bears S.31°W., 13.3 ft.

5" dia. D.Fir, double blazed and scribed "T31S R7W S27 CS BT" bears S.33°E., 9.7 ft.

11" dia. Pine, double blazed and scribed "T31S R7W S22 CS BT" bears N.0½°E., 74.3 ft.