

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 21 and 22

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 448 dated June 13, 1882 (DCSO records Vol. 19 Page(s) 8058)

Set Pine post 40" long, 4" sq., 18" in the ground, marked ¼ S. on W. side for the ¼ sec. cor., from which
A Pine 36" dia., bears S.50°W., 244 lks. dist. mkd. ¼ S BT.
A Pine 42" dia., bears S.58°E., 206 lks. dist. mkd. ¼ S BT.

BLM resurvey by Donald Beck, Cadastral Surveyor, under Group #531 - Surveyed Oct 1963/June 1964 - (DCSO records Vol. 33 Page(s) 13634-35)

The ¼ sec. cor., determined from the remains of the original bearing trees:

A Pine 60" dia., bears S.58°E., 206 lks. dist. mkd. S on bark blaze.

A Pine snag 45" dia., bears S.50°W., 194 lks. dist. with no marks remaining. (Rec. dist. 244 lks.)

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

T 31 S R 7 W
¼
S 21 | S 22
1964

from which new bearing trees:

A Fir 18" dia., bears N.26¼°E., 43 lks. dist. mkd. ¼ S22 BT.

A Fir 16" dia., bears N.87½°W., 31 lks. dist. mkd. ¼ S21 BT.

Douglas Co. Surveyors Office - Randall Smith, Stephen Flause, Sept. 10, 1996 - C.S. File 65/9-11

Found - 3¼" Brass cap (1964 BLM) on a 2½" O.D. iron pipe, protrudes 4" above ground.

Accessories Found -

36" now 38" dia. 25 ft. high Pine snag, no scribing visible (bark is gone), bears S.52½°W., 128.0 ft. (rec. S.50°W., 128 ft. per 1964 BLM) O.B.T.

42" now 55" dia. 80 ft. high Pine snag, no scribing visible, bears S.58°E., 137.2 ft. (rec. S.58°E., 136.0 ft., dist. would fit well to orig. scribing, now gone) O.B.T.

18" now 27" dia. D.Fir with a fully healed single blaze bears N.26¼°E., 28.4 ft. (agrees with rec.) 1964 BLM
(Cont. Next Page)

TOWNSHIP 31 RANGE 07 POINT IDENTIFIER # 400340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 21 and 22

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

Accessories Found Continued -

16" now 26" dia. D.Fir with a fully healed single blaze,
bears N.87½°W., 20.5 ft. (agrees with rec.) 1964 BLM

New Accessories -

14" dia. D.Fir, double blazed and scribed "¼ S22 CS BT"
bears S.3½°E., 10.9 ft.

27" dia. D.Fir, double blazed and scribed "¼ S22 CS BT"
bears N.4°E., 11.1 ft.

Ron Quimby - Crew: R. Olsen & J. Leonard - 10/2017 - C.S.
File 65/99-26

Found - BLM brass cap on 2½" I. Pipe (properly mkd)
38" Pine snag S.52°W., 128.0 ft. (no marks)
55" Pine stump S.58°E., 137.2 ft. (no marks)
27" Fir stump N.26°E., 28.4 ft. healed blaze.
29" Fir N.87°W., 20.5 ft. healed scar.
16" Fir S.3°E., 10.9 ft. healed scar.

New - 6" Fir S.70°E., 5.9 ft. scribed ¼ S22 BT.

Note - Corner is approx. 450' South of a Creek flowing SE.
Area burnt 9/2017
Compass decl. 15½°E.