

TOWNSHIP 31 RANGE 07 POINT IDENTIFIER # 400440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 15 and 16

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 448 dated June 13, 1882 (DCSO records Vol. 19 Page(s) 8060)

Set stone 14x12x5, 10" in the ground for ¼ sec. cor. marked ¼ on W. face, from which

A Fir 12" dia., bears S.55°E., 10 lks. dist. mkd. ¼ S BT.

A Fir 10" dia., bears N.70°W., 11 lks. dist. mkd. ¼ S BT.

Douglas Co. Surveyors Office - John M. Powell - 06/1969 - C.S. File 54/36-21 & 23 - added 5/28/2014 DCSO JC

Reported as not found

Found old N-S blazes opened blazes, ring count old enough for orig.

2 small BTs, it seems as if cor. should be there but I did not find it - call on creek 626.0 to the south.

BLM resurvey by Owen C. Chatters II, Cadastral Surveyor, under Group #834, surveyed April/June 1974 - (DCSO records Vol. 39 Page(s) 15741)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28" long, 2 1/2" dia., 22" in the ground, with brass cap mkd:

T 31 S R 7 W

¼
S 16 | S 15
1974

from which

A Fir 12" dia., bears S.76½°E., 37 lks. mkd. ¼ S15 BT.

A Fir 18" dia., bears S.73¼°W., 59 lks. mkd. ¼ S16 BT.