TOWNSHIP 31 RANGE 07 POINT IDENTIFIER # 400640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 3 and 4

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor, under Contract #152, dated June 3, 1871, - (DCSO records Vol. 19 Page(s) 8020)

Set ¼ sec. post, from which
A Laurel 24" dia., bears S.40°E., 30 lks.
A Laurel 8" dia., bears N.80°W., 11 lks.

GLO survey by Gerald A. Sorrels, U.S. Surveyor, under under Special Instructions dated March 1, 1917 - (DCSO records Vol. 19 Page(s) 8085-86) and duplicated info. in Vol. 27 Pg. 11633)

The old ¼ sec. cor., located by reference to the bearing trees. At the exact cor. point
Set an iron post, 3 ft. long, 1" dia., 26" in the ground, for ¼ sec. cor., with brass cap marked: ¼
S 4 S 3
1918
from which
A Madrona 24" dia., bears S.67°E., 32 lks. dist. mkd. ¼ S3 BT. (Old BT)
A Madrona 12" dia., bears N.84°W., 10 lks. dist. mkd. ¼ S4 BT. (Old BT)

Douglas Co. Surveyors Office - James W. Byron, Deputy - Ray Irving; John Fee, crew - Work done for: Robert M. King - Sept. 21, 1954 - C.S. File 46/38

Found - Brass cap.
8" Laurel, N.80°W., 11 lks. dist., dead.
24" Laurel, S.65°E., 30 lks. dist., in good condition. (S.40°E. 30 lks. per record.)
Blazed and scribed:
10" R.Fir S.10°W., 49.2 ft., mkd. ¼ S4 CS BT.

Fd. OK, Feb. 6, 1981 by H.Johnstone - M 86-62 & M 97-61