

TOWNSHIP 31 RANGE 07 POINT IDENTIFIER # 440200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 27 and 34

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by W.H. Byars, Deputy Surveyor under contract # 448 dated June 13, 1882 (DCSO records Vol. 19 Page(s) 8056)

Set Pine post 3 ft. long, 4" sq., 18" in the ground for the 1/4 sec. cor. marked 1/4 S. on N. face, from which
A Pine 14" dia., bears S.70°W., 21 lks. dist. mkd. 1/4 S BT
A Pine 26" dia., bears N.5°W., 69 lks. dist. mkd. 1/4 S BT

Survey by Howard W. Johnstone, LS #498 - For: Roseburg Lumber Co. - Aug/Sept. 1962 - C.S. File 51/163-11

Found - 14" Pine S.70°W., 13.9 ft., down.
26" Pine N.5°W., 45.5 ft, snag.
Set 1" x 30" Iron pipe.
Scribed- 5" D.Fir N.43 1/2°W., 8.5 ft.
32" Pine S.87°E., 54.6 ft.

BLM resurvey by Donald Beck, Cadastral Surveyor, under Group #531 - Surveyed Oct 1963/June 1964 - (DCSO records Vol. 33 Page(s) 13630-31)

The 1/4 sec. cor. recorded and remonumented in 1962 by Johnstone, with a wooden stake, 6 ft. long, 2" sq., firmly set 12" in the ground, from which the remains of the original bearing trees:

A Pine snag 35" dia., bears N.5°W., 69 lks. dist., with no marks visible.

A down Pine 14" dia., bears S.70°W., 21 lks. dist., with illegible scribe marks visible on opened and burned double blaze.

and bearing trees mkd. by Johnstone:

A Fir 8" dia., bears N.45°W., 13 lks. dist. mkd. with a partially healed double blaze.

A Pine 35" dia., bears S.87°E., 83 lks. dist. mkd. with a partially healed blaze.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

T 31 S R 7 W

1/4 S 27
S 34
1964