

TOWNSHIP 31 RANGE 07 POINT IDENTIFIER # 440400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 15 and 22

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by W.H. Byars, Deputy Surveyor under contract # 448 dated June 13, 1882 (DCSO records Vol. 19 Page(s) 8059)

-----  
Set a Fir post 40" long, 3" sq., 18" in the ground, marked  $\frac{1}{4}$  S. on N. side for the  $\frac{1}{4}$  sec. cor., from which

A Laurel 16" dia., bears N.62°W., 32 lks. dist. mkd.  $\frac{1}{4}$  S BT.

A Laurel 10" dia., bears S.20°W., 26 lks. dist. mkd.  $\frac{1}{4}$  S BT.

BLM resurvey by Owen C. Chatters II, Cadastral Surveyor, under Group #834, surveyed April/June 1974 - (DCSO records Vol. 39 Page(s) 15740)

-----  
Point for the  $\frac{1}{4}$  sec. cor., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28" long, 2 1/2" dia., 22" in the ground, with brass cap mkd:

T 31 S R 7 W

$\frac{1}{4}$   $\frac{S 15}{S 22}$

1974

from which

A Fir 13" dia., bears N.22°W., 52 lks. dist. mkd.  $\frac{1}{4}$  S15 BT

A Fir 26" dia., bears S.3 $\frac{1}{2}$ °E., 9 lks. dist. mkd.  $\frac{1}{4}$  S22 BT.

Ron Quimby - Crew: R. Olsen & J. Leonard - 10/2017 - C.S. File 65/99-46

-----  
Found - BLM brass cap on 2 $\frac{1}{2}$ " I.Pipe

30" Fir S.3°E., 6.0 ft. (healed face dead)

18" Fir N.22°W., 34.3 ft. (healed face dead)

28" Fir N.50°E., 7.3 ft. visible scribes (no record)

New - 32" Madrona S.82°E., 32.0 ft. scribed  $\frac{1}{4}$  S22 BT

26" Madrona N.19°E., 18.8 ft. scribed  $\frac{1}{4}$  S15 BT

$\frac{5}{8}$ " I.Rod with yellow plastic cap S.67°W., 17.0 ft. post alongside.

$\frac{5}{8}$ " I.Rod with yellow plastic cap N.43°W., 12.2 ft. post alongside.

Note - Area badly burnt 9/2017

Compass decl. 15 $\frac{1}{2}$ °E.