

TOWNSHIP 31 RANGE 07 POINT IDENTIFIER # 440600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 3 and 10

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor, under Contract #152, dated June 3, 1871, - (DCSO records Vol. 19 Page 8018)

Set ¼ sec. post, from which
A Fir 10" dia., bears N.60°E., 8 lks.
A Fir 14" dia., bears S.45°W., 17 lks.

Douglas County Surveyors Office - Gary Langlitz and Pete Earle, crew - April 25, 1974 - C.S. File 56/51-1

Found both original bearing trees. It was found that the original BTs stand far enough apart that the record distances as measured from these trees do not intersect. Therefore, the following procedure was followed: A temporary point was set at record bearing and distance from each BT. The distance between the two temporary points was divided in half and at this point we

Set a brass cap for the ¼ corner mkd: County Surveyors Office

S 3 1/4

S 10
T 31 S R 7 W
1974

from which original BTs

10" now 14" D.Fir bears N.68°E., 6.3 ft. (Rec. N.60°E., 5.3 ft.) scribing "S" visible on previously opened blaze.

Orig. 14" now 24" D.Fir bears S.50°30'W., 11.8 ft. (Rec. S.45°W., 11.2 ft.) We open and find scribing "1/4".

and a New BT

14" D.Fir bears S.42°E., 17.8 ft. scribed "¼ S10 CS BT"

Cor. Fd. and used in BLM resurvey by Owen C. Chatters II, Cadastral Surveyor, under Group #834, surveyed April/June 1974 - (DCSO records Vol. 39 Page(s) 15744-45)

Cor. Fd. and used in BLM resurvey by Wayne L. Rogers, Cadastral Surveyor, Group #834, surveyed July 1979 - (DCSO records Vol. 42 Page(s) 16556)

Ron Quimby - Crew: N. Fromdahl & R. Heilchel - 12/2017 - C.S. File 65/99-40

Found - DCSO 2½" brass cap (properly mkd)
16" Fir snag N.68°E., 6.3 ft. good scar.
18" Fir snag S.42°E., 17.8 ft. good scar.
New - 26" Fir North 48.8 ft. bark scribed ¼ S3 BT.
38" Fir N.44°E., 66.6 ft. scribed ¼ S3 BT.
continued next page

TOWNSHIP 31 RANGE 07 POINT IDENTIFIER # 440600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 3 and 10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

5/8" I.Rod with yellow plastic cap S.33°E., 14.0 ft.
post alongside.
5/8" I.Rod with yellow plastic cap S.32°W., 15.8 ft.
post alongside.
Note - Corner is approx. 150' west of Rd. 31-7-10.3
Area badly burnt 9/2017
Compass decl. 15½°E.