

TOWNSHIP 31 RANGE 07 POINT IDENTIFIER # 440700

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 3; & 34 of T30-7

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor, under Contract #152, dated June 3, 1871, - (DCSO records Vol. 17 Page(s) 7230)

Set ¼ sec. post, from which
A Pine 24" dia., bears N.50°E., 32 lks. dist.
A Laurel 20" dia., bears S.65°E., 44 lks. dist.

Survey by John H. Markham, Jr. - Wit: Geo. Vaughn; P.J. Holmes - June 21, 1951 - C.S. File 40/311

Location determined by a pile of stones and old BT:
A Pine snag 30" dia., N.50°E., 21.0 ft. with scribe marks.
A Laurel, dead, 24" dia., S.68°E., 29.0 ft.
Drove a 1" x 30" Iron pipe for corner, from which
A Pine 12" dia., bears S.49°E., 49.0 ft. scribed ¼ S3 BT
A Fir 52" dia., bears North, 225 ft. scribed ¼ S34 BT.
Corner lies in an old burn on a little flat on the nose of a ridge.

Douglas Co. Surveyors Office - James Byron, Deputy - Mike Darby; Jim Halterman, crew - Feb. 1964 - C.S. File 53/40-49

Found - 1" I.P. and mound of stone at corner.
Now 16" Pine BT, S.49°E., 49.0 ft.
New BT - 17" Cedar bears S.43°W., 99.8 ft. scribed ¼ S3 CSBT

Douglas County Surveyors Office - R.B. Kimberling; M.W. Cline, crew - Oct. 27, 1977 - C.S. File 59/40-56

Found - 1" Iron pipe in a mound of stone.
12" now 23" Sugar Pine, bears S.49°E., 49.0 ft. with a well healed double blaze.
17" now 16" Incense Cedar bears S.43°W., 99.8 ft. with visible scribed "¼ S3 CS BT" in a partially healed double blaze.
Set a 1" x 36" Iron pipe with a brass cap set 9" above ground, in mound of stone and iron pipe alongside, marked "Douglas County Surveyors T30S R7W ¼ S34 S3 T31S R7W 1977".
No new accessories.
Corner lies in old unit, 50 ft. North of tree line.

Fd. OK March 1994 by Ron Quimby - M 119-21