

TOWNSHIP 31 RANGE 07 POINT IDENTIFIER # 500140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 34 and 35

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by W.H. Byars, Deputy Surveyor under contract # 448 dated June 13, 1882 (DCSO records Vol. 19 Page(s) 8046)

-----  
Set a Laurel post, 3 ft. long, 3" sq., 18" in the ground for 1/4 sec. cor. marked 1/4 S. on W. face, from which  
A Laurel 12" dia., bears S.30°W., 36 lks. mkd. 1/4 S BT.  
A Laurel 5" dia., bears S.50°E., 22 lks. mkd. 1/4 S BT.

BLM resurvey by Donald Beck, Cadastral Surveyor, under Group #531 - Surveyed Oct 1963/June 1964 - (DCSO records Vol. 33 Page(s) 13624)

-----  
Point for the 1/4 sec. cor., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

T 31 S R 7 W  
1/4  
S 34 | S 35  
1964

from which

A Fir 16" dia., bears S.14°E., 88 lks. mkd. 1/4 S35 BT  
A Fir 17" dia., bears S.75 1/2°W., 77 1/2 lks. mkd. 1/4 S34 BT.

Survey by Howard Johnstone - For: Roseburg Lumber Co. - Feb. 5, 1985 - C.S. File 58/296-1

-----  
Found - 1964 Cadastral brass cap.

16" D.Fir S.14°E., 58.1 ft. (1964)

New BT - 3 1/2" D.Fir S.41°W., 13.8 ft. scribed 1/4 S34 BT.

Set steel fence post alongside brass cap.

Corner is on East slope, partly buried, on the lower side of a dirt fill from a cat fire trail road.

Dan Saily - For: Lone Rock LLC - Crew: Brett Ragon, Brodie Minter - Ignacio Roman, Zachary Holland & Trevor Clemo - 12/2024 - M184-40

-----  
Found - 1964 BLM brass cap and iron pipe (properly mkd)

28" D.Fir bears S.14 1/4°E., 57.4' (1985 rec. S.14°E., 58.1') with a healed face and BLM tag.

11"x6' tall D.Fir stump bears S.37°W., 13.4' (1985 rec. S.41°W., 13.8') with a healed face and Roseburg Lumber Co. tag.

Set - 5/8"x36" iron rod reference, 0.2' above ground, with orange plastic cap mkd: LONE ROCK TIMBER 85006PLS bears N.26°28'08"E., 31.94'. We place a 5/2' steel galvanized U-Post beside and wire tag to post.

Continued next page

TOWNSHIP 31 RANGE 07 POINT IDENTIFIER # 500140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 34 and 35

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

Set - 5/8"x36" iron rod reference, 0.2' above ground, with orange plastic cap marked LONE ROCK TIMBER 85006PLS bears N.54°14'32"W., 16.39'. We place a 5½' steel galvanized U-Post beside and wire tag to post.

Note - Found bent steel post along north side of monument corner monument lies on east facing slope at SE edge of recent clear-cut, with mature timber to the SE. Top of monument is at ground level with dozer trail fill material perched above to the north and west. we place a 5½' tall steel galvanized U-Post 0.2' north.