

TOWNSHIP 31 RANGE 07 POINT IDENTIFIER # 500300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 22, 23, 26 and 27

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by W.H. Byars, Deputy Surveyor under contract # 448 dated June 13, 1882 (DCSO records Vol. 19 Page(s) 8048)

Set Fir post 4 ft. long, 4" sq., 24" in the ground for the cor. to secs. 22, 23, 26 and 27, marked T31S R7W S23 on NE.; S26 on SE.; S27 on SW. and S22 on NW. faces, with 2 notches on E. and S. edges, from which

- A Fir 8" dia., bears N.36°E., 21 lks. dist. mkd. T31S R7W S23 BT.
- A Fir 12" dia., bears S.48°E., 25 lks. dist. mkd. T31S R7W S26 BT.
- A Fir 12" dia., bears S.14°W., 29 lks. dist. mkd. T31S R7W S27 BT.
- A Fir 10" dia., bears N.68°W., 33 lks. dist. mkd. T31S R7W S22 BT.

Survey by Howard W. Johnstone, LS #498 - For: Roseburg Lumber Co. - Aug/Sept. 1962 - C.S. File 51/163-11

-
- Found - 8" Fir N.36°E., 13.9 ft., dead.
12" Fir S.48°E., 16.5 ft., down.
12" Fir S.14°W., 19.1 ft., down.
10" Fir N.68°W., 21.8 ft., good.
- Scribed - 12" D.Fir N.5½°E., 11.3 ft.
18" D.Fir S.14°W., 25.5 ft.
11" D.Fir S.9°E., 50.0 ft.

BLM resurvey by Donald Beck, Cadastral Surveyor, under Group #531 - Surveyed Oct 1963/June 1964 - (DCSO records Vol. 33 Page(s) 13627-28)

The Sec. Cor., recorded and remonumented in 1962 by Johnstone with a wooden stake, 4 ft. long, 3" sq., firmly set, 12" in the ground, from which the remains of the original bearing trees:

- A down Fir snag 8" dia., bears N.36°E., 21 lks. dist., with no marks visible on opened blaze.
- A down Fir 20" dia., bears S.48°E., 25 lks. dist. mkd. with a healed blaze.
- A down Fir 12" dia., bears S.14°W., 29 lks. dist. with no marks visible.
- A Fir 21" dia., bears N.68°W., 33 lks. dist. mkd. with a healed blaze.

and bearing trees marked by Johnstone:
A Fir 12" dia., bears N.10½°E., 17 lks. dist. mkd. with a partially healed double blaze.

(Cont. Next Page)

TOWNSHIP 31 RANGE 07 POINT IDENTIFIER # 500300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 22, 23, 26 and 27

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

A Fir 13" dia., bears S.9½°E., 75 lks. dist. mkd. with a partially healed double blaze.

A Fir 20" dia., bears S.14°W., 37 lks. dist. mkd. with a partially healed double blaze.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

T 31 S R 7 W
S 22 | S 23
S 27 | S 26
1964

Reset the wooden stake alongside the iron post.

BLM resurvey by Owen C. Chatters II, Cadastral Surveyor, under Group #834, surveyed April/June 1974 - (DCSO records Vol. 39 Page(s) 15732-33)

The Sec. cor., monumented with an iron post 2½" dia., firmly set, projecting 6" above ground, with brass cap mkd. in 1964, from which the remains of the original bearing trees:

A root hole bears N.36°E., 21 lks. dist., with a down Fir alongside, 8" dia., with healed blaze.

A root hole bears S.48°E., 25 lks. dist., with a down double trunked Fir alongside, 25" dia., with healed blaze.

A root hole bears S.14°W., 29 lks. dist., with a down Fir alongside, 12" dia., with decayed blaze.

A Fir 25" dia., bears N.68°W., 33 lks. dist., with healed blaze.

and the remains of bearing trees mkd. by Johnstone:

A root hole bears N.10¼°E., 17 lks. dist. with a down Fir alongside, 13" dia., with scribe marks T31S R7W S23 BT visible on open double blaze.

A Fir 13" dia., bears S.9½°E., 75 lks. dist., with healed double blaze.

A Fir 22" dia., bears S.14°W., 37 lks. dist., with healed double blaze.

and a new bearing tree:

A Fir 11" dia., bears N.2 3/4°W., 118 lks. dist., mkd. T31S R7W S22 BT.