

TOWNSHIP 31 RANGE 07 POINT IDENTIFIER # 500340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 22 and 23

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 448 dated June 13, 1882 (DCSO records Vol. 19 Page(s) 8050)

Set a Fir post 3 ft. long, 3" sq., 18" in the ground for ¼ sec. cor. marked ¼ S. on W. face, from which
A Fir 48" dia., bears East, 25 lks. dist. mkd. ¼ S BT.
A Fir 6" dia., bears S.68°W., 25 lks. dist. mkd. ¼ S BT.

BLM resurvey by Owen C. Chatters II, Cadastral Surveyor, under Group #834, surveyed April/June 1974 - (DCSO records Vol. 39 Page(s) 15733-34)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

T 31 S R 7 W

¼
S 22 S 23
1974

from which

A Fir 48" dia., bears East, 25 lks. dist. mkd. ¼ S23 BT.

A Fir 6" dia., bears S.68°W., 25 lks. dist. mkd. ¼ S22 BT.