

PRIMARY CORNER DESCRIPTION Center 1/4 Cor for Sec 35

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

BLM resurvey by Donald Beck, Cadastral Surveyor, under Group #531 - Surveyed Oct 1963/June 1964 - (DCSO records Vol. 33 Page(s) 13644-45)

Point for the center 1/4 sec. cor. of sec. 35, at intersection with the E. and W. center line.

Set an iron post 28" long, 2½" dia., 22" in the ground, with brass cap mkd: C¼ S 35
1964

from which

A Fir 26" dia., bears N.34°E., 65 lks. dist. mkd. C¼ S35 BT.

A Fir 21" dia., bears S.53°W., 25 lks. dist. mkd. C¼ S35 BT.

Survey by Howard W. Johnstone, LS #498 - For: Roseburg Lumber Co. - Aug. 14, 1986 - C.S. File 63/26-5

Found - 1964 Cadastral brass cap, properly marked.
26" Fir N.34°E., 42.9 ft., now stump. Drove 3/8" sq. x 12" boat spike in center of stump.
21" Fir, S.53°W., 16.5 ft., now stump. Drove 3/8" sq. x 12" boat spike in center of stump. Stump is covered with light sheet metal, painted white.

New Accessories:

28" D.Fir stump, drove 3/8" sq. x 12" boat spike in center, N.21°W., 28.3 ft.

Set a 4 ft. light weight fence post alongside the brass cap.

Corner falls in the middle of clear cut limit. No trees suitable for new BTs.

Dan Saily - For: Lone Rock LLC - Crew: Brett Ragon, Brodie Minter - Ignacio Roman, Zachary Holland & Trevor Clemo - 12/2024 - M184-40

Found - 1964 BLM brass cap and iron pipe (properly mkd)
Indeterminate size rotten D.Fir stump bears N.21¼°W., 28.3' to a spike in the top center (1986 rec N.21°W., 28.3').
Tin covered Fir stump bears S.53½°W., 22.8' (1963-4 rec S.53°W., 16.5') with BLM tag and spike.

New - 12" D.Fir bears N.28½°W., 28.5'. We scribe C¼ S35 BT and tag.

9" D.Fir bears S.43°W., 17.2'. We scribe C¼ S35 BT and tag.

8" D.Fir bears S.52¾°E., 23.1'. We scribe C¼ S35 BT and tag.

Continued next page

TOWNSHIP 31 RANGE 07 POINT IDENTIFIER # 540140

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. for Sec. 35

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

8" D.Fir bears N33 3/4°E 24.9'. We scribe C¼ S35 BT and tag.
Note - BTs were scribed at root crown with distances measured to an aluminum nail at side center.

Steel post along north side of monument.
Corner monument lies on steep NE facing slope in even aged second growth timber stand. Top of monument is at ground level.