

TOWNSHIP 31 RANGE 07 POINT IDENTIFIER # 600200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 25, 26, 35 and 36

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by W.H. Byars, Deputy Surveyor under contract # 448 dated June 13, 1882 (DCSO records Vol. 19 Page(s) 8036)

-----  
Set a Pine post, 4 ft. long, 4" sq., 24" in the ground, for cor. to secs. 25, 26, 35 and 36, marked T31S R7W S25 on NE.; S36 on SE.; S35 on SW.; and S26 on NW. faces, with 1 notch on E. and S., edges, from which

- A Pine 32" dia., bears N.42°E., 72 lks. dist. mkd. T31S R7W S25 BT.
- A Pine 34" dia., bears S.25°E., 7 lks. dist. mkd. T31S R7W S36 BT.
- A Pine 28" dia., bears S.70°W., 66 lks. dist. mkd. T31S R6W S35 BT.
- A Pine 18" dia., bears N.28°W., 39 lks. dist. mkd. T31S R7W S26 BT.

Survey by Clifford M. Bryden - For: Roseburg Lumber Co. - Feb. 14, 1957 - C.S. File 42/249

-----  
Found - Old BT, Yellow Pine 24", N.29°W., 25.4 ft.  
4"x4"x4 ft. Post, squared, at corner.  
New BTs - 6" Fir N.30°E., 11.0 ft. scribed R.E. 3937 BT.  
6" Fir S.84°W., 13.5 ft. scrobed R.E. 3937 BT.

Survey by Howard W. Johnstone - For: Roseburg Lumber Co. - May 28, 1962 - C.S. File 51/163-1

-----  
Found four good bearing trees, renewed in 1957.  
Set 1" x 30" Iron pipe.

Douglas Co. Surveyors Office - James Byron, Deputy - Mike Darby; crew - May 31, 1963 - C.S. File 49/109-17

-----  
Found - 1" I.P. at corner.  
Orig. 18" now 30" Pine, N.28°W., 25.7 ft., shows good scribing.  
Low cut stump of original SE. BT.  
Both BTs as recorded by Bryden.  
New BT - 12" R.Fir bears S.39°E., 34.0 ft. scribed S36 R7W CS BT.  
Old road is South 20 ft.

BLM resurvey by Donald Beck, Cadastral Surveyor, under Group #531 - Surveyed Oct 1963/June 1964 - (DCSO records Vol. 33 Page(s) 13623)

-----  
The Sec. cor., remonumented with an iron pipe, 1" dia., 6" above ground, firmly set. (Cont. Next Page)

TOWNSHIP 31 RANGE 07 POINT IDENTIFIER # 600200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 25, 26, 35 and 36

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Perpetuations of the corner were made by Bryden in 1957, Johnstone in 1962, and Byron in 1963. From the iron pipe, the original bearing trees:

A Pine snag 40" dia., bears N.38°E., 72 lks. dist., no marks remaining. (Rec. N.42°E.)

A Pine stump 42" dia., bears S.52°E., 9 lks. dist. (7 lks. to face), no marks remaining. (Rec. dist. 7 lks.)

A Pine 24" dia., bears N.31°W., 39 lks. dist. mkd. 7W S26 on open blaze. (Rec. N.28°W.)

bearing trees mkd. by Bryden in 1957:

A Fir 9" dia., bears N.29°E., 16½ lks. dist. mkd. with a partially healed double blaze.

A Fir 7" dia., bears S.82°W., 20½ lks. dist. mkd. with a partially healed double blaze.

and a bearing tree mkd. by Byron in 1963:

A Fir 13" dia., bears S.39°E., 52 lks. dist. mkd. T31S R7W S36 CS BT on double blaze.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 23" in the ground, with brass cap mkd:

T 31 S R 7 W  
S 26 | S 25  
S 35 | S 36  
1964

from which a new bearing tree:

A Fir 10" dia., bears N.54½°W., 57 lks. dist. mkd. T31S R7W S26 BT.

Reset the iron pipe alongside the iron post.

Fd. OK, Oct. 19, 1977 by DCS0 - C.S. File 59/40-50

Fd. OK, July 1994 by M. Smalley - M 120-43