

TOWNSHIP 31 RANGE 07 POINT IDENTIFIER # 600240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 25 and 26

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by W.H. Byars, Deputy Surveyor under contract # 448 dated June 13, 1882 (DCSO records Vol. 19 Page(s) 8038)

Set Laurel Post, 3 ft. long, 3" sq., 18" in the ground for 1/4 sec. cor. marked 1/4 S. on W. face, from which
A Live Oak 14" dia., bears N.32°W., 85 lks. dist. mkd. 1/4 S BT.
A Sugar Pine 44" dia., bears S.10°E., 84 lks. dist. mkd. 1/4 S BT.

Survey by Howard W. Johnstone - For: Roseburg Lumber Co. - May 28, 1962 - C.S. File 51/163-1

Found - Live Oak N.32°W., 56.1 ft., good condition.
S.Pine S.10°E., 55.4 ft., now 60" snag.
Set 1" x 30" Iron pipe.
Scribed -6" D.Fir S.70½°E., 11.0 ft.

Douglas County Surveyors Office - R.B. Kimberling; M.W. Cline, crew - Oct. 20, 1977 - C.S. File 59/40-53

Found - A 1" x 30" Iron pipe, 24" in ground.
A 14" now 23" Live Oak bears N.32°W., 56.1 ft., with single chopped out blaze. (OBT)
A 44" now 54" Pine stump, barked, bears S.7°E., 54.1 ft. (Rec. S.10°E., 55.4 ft.)
A 6" now 10" D.Fir bears S.70½°E., 11.0 ft. with double well healed blaze.
Set a 1" x 36" iron pipe with brass cap set 7" above ground and marked:
Douglas County Surveyor
T 31 S R 7 W
1/4
S 26 | S 25
1977
Set 1" x 30" I.P. under North edge of brass cap.
No new accessories. To reach: Take left fork of Smith Creek Road to end. Corner bears NW ± 800 ft., 50 ft West of West edge of clear cut unit.