

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GL0 survey by W.H. Byars, Deputy Surveyor under contract # 448 dated June 13, 1882 (DCSO records Vol. 19 Page(s) 8038)

-
- Set a Pine post 4 ft. long, 4" sq., 24" in the ground, for the cor. to secs. 23, 24, 25 and 26, marked T31S R7W S24 on NE.; S25 on SE.; S26 on SW.; and S23 on NW. faces, with 1 notch on E. and 2 notches on S. edges, from which
- A Pine 8" dia., bears N.44°E., 55 lks. dist. mkd. T31S R7W S24 BT.
 - A Fir 34" dia., bears S.40°E., 29 lks. dist. mkd. T31S R7W S25 BT.
 - A Laurel 6" dia., bears S.54°W., 22 lks. dist. mkd. T31S R7W S26 BT.
 - A Fir 12" dia., bears N.70°W., 23 lks. dist. mkd. T31S R7W S23 BT.

Survey by Howard W. Johnstone - For: Roseburg Lumber Co. - Jan. 30, 1963 - C.S. File 51/163-6

-
- Found - 34" Fir S.40°E., 19.1 ft., bark scribed and now a snag.
- Set 1" x 30" Iron pipe.
- Scribed -12" Cedar N.62½°E., 25.9 ft.
- 6" Fir S.78°E., 11.2 ft.
 - 34" Fir S.6°W., 43.0 ft.
 - 5" Fir N.9°W., 20.7 ft.

Douglas Co. Surveyors Office - Randall Smith, Stephen Flause, Sept. 1996 C.S. File 65/9-8

-
- Found - Bent 1" I.D. iron pipe protrudes 1 ft. above ground. I.P. bent in a southwest direction. (1963)
- Accessories Found -
- 34" now 24" dia. 2 ft. high rotted D.Fir stump, bark is off, no scribing found, bears S.40°E., 20.5 ft. to center (rec. S.40°E., 19.1 ft., dist would fit well to bark) O.B.T.
 - No other orig. BT's Found.
 - 6" now 6" dia. 1 ft. high rotted D.Fir stump, scribing found "BT" bears S.78°E., 11.2 ft. (agrees with rec.) 1963.
 - 34" now 38" dia. 5½ ft. high D.Fir stump, with a fully healed double blaze, bears S.7½°W., 43.0 ft. (rec. S.6°W., 43.0 ft.) 1963.
 - 1963 NW BT is now gone.
 - 12" now 13" dia. 3 ft. high rotted cedar stump with scribing visible "S24 BT" bears N.62½°E., 25.9 ft. (agrees with rec.) 1963. (Cont. Next Page)

TOWNSHIP 31 RANGE 07 POINT IDENTIFIER # 600300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 23, 24, 25 and 26

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Monument Set - 2 3/8" dia. brass cap on a 1 3/8" O.D. by 32" long iron pipe is set at plumb position of found iron pipe, protrudes 6" above ground.

- Found iron pipe is 31" long and is set along north edge of BC/IP, protrudes 10" above ground.

- Brass cap set at corner point marked:

Douglas County Surveyors

T 31 S R

S 23 | S 24 7

S 26 | S 25 W

Office 1996

New Accessories -

5" dia. D.Fir, double blazed and scribed "T31S R7W S25 CS BT" bears S.75°E., 14.9 ft.

10" dia. D.Fir, double blazed and scribed "T31S R7W S23 CS BT" bears N.23½°W., 49.5 ft.

3" dia. D.Fir, double blazed and scribed "X BT" bears N.11°E., 3.0 ft.