

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 23 and 24

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 448 dated June 13, 1882 (DCSO records Vol. 19 Page(s) 8040)

A Pine tree, 16" dia., which I marked ¼ S. on W. face for ¼ sec. cor., from which

A Cedar 34" dia., bears N.80°E., 46 lks. dist. mkd. ¼ S BT

A Cedar 12" dia., bears N.39°W., 34 lks. dist. mkd. ¼ S BT

Douglas Co. Surveyors Office - John M. Powell, Frank Jones, Cliff Stone, crew - Dec. 1966 - C.S. File 54/36-9

Found - 12" now 14" Cedar N.39°W., (brg. should be N.27°W). Scribe visible, "¼ S BT". Rings too fine to count.
34" now 46" Cedar N.80°E., 30.4 ft., shows good scar. (find this brg. to be N.71½°E.)
16" Pine corner tree, now 27". Find no scribing on this tree.

Set Brass cap on West side of Corner tree marked:

County Surveyors Office

T 31 S R 7 W

¼ S 23 | S 24

1966

Bearing trees OK and tagged. Corner lies very good for call at 45.50 chains, going North.

Douglas Co. Surveyors Office - Randall Smith, Stephen Flause, Sept. 5, 1996 - C.S. File 65/9-10

Found - 16" now 27" dia. 7' high Pine stump. We open further than 1966 DCSO renewal, no scribing found. (orig. corner tree).

- 2½" dia. brass cap on a 1½" O.D. iron pipe, protrudes 18" above ground. Found along west edge of orig. corner tree. (1966 DCSO)

- Center or corner tree bears East, 1 ft.

Accessories Found - Bearings & distances from corner tree

12" now 16" dia. Cedar with an unhealed blaze, scribing visible "¼ S" bears N.27°W., 23.1 ft. (1966 rec. N.27°W., 22.4 ft. possible face measurement) O.B.T.

34" now 46" dia. 8 ft. high Cedar stump, no blaze visible, bears N.71½°E., 30.4 ft. (agrees with 1966 rec.) O.B.T.

Bearings & distances from BC/IP to O.B.T's -

16" dia. Cedar bears N.26½°W., 23.1 ft.

46" dia. Cedar stump bears N.73°E., 30.9 ft.

New accessories - Bearings & distances taken from BC/IP

7" dia. D.Fir, double blazed and scribed "¼ S24 CS BT" bears N.11½°E., 10.9 ft.

(Cont. Next Page)

TOWNSHIP 31 RANGE 07 POINT IDENTIFIER # 600340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 23 and 24

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

8" dia. Pistol butt D.Fir, double blazed and scribed "¼ S23 CS BT" bears N.79°W., 11.7 ft. to center of trunk.
5" dia. D.Fir, double blazed and scribed "¼ S24 CS BT" bears S.17°E., 29.5 ft.

Fd. Ok by R Quimby - 10/2017 - C.S. File 65/99-12