

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1, 2, 11 and 12

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by W.H. Byars, Deputy Surveyor, under Contract #152, dated June 3, 1871, - (DCSO records Vol. 19 Page(s) 8019)

Set post cor. to secs. 1, 2, 11 and 12, from which
A Fir 12" dia., bears N.70°E., 67 lks.
A Maple 10" dia., bears S.50°E., 35 lks.
A Maple 10" dia., bears S.18°W., 40 lks.
A Fir 60" dia., bears N.65°W., 54 lks.

Fd. and used cor. in GLO survey by Byars, under Group #448, dated June 1882 - (DCSO records Vol. 19 Page(s) 8044)

BLM resurvey by James E. Jelley, Cadastral Surveyor, under Group #'s 350 and 680 - Surveyed April/Sept. 1969 - (DCSO records Vol. 35 Page(s) 14505)

The Sec. cor., determined at record distance from the remaining original bearing trees:
A root hole bears N.70°E., 67 lks. dist., with a down Fir, 27" dia., alongside, with fragmentary scribe marks visible on open blaze.
A Maple 15" dia., bears S.14°W., 40 lks. dist. with healed blaze. (Record, S.18°W.)
A burned out Fir stump, 70" dia., bears N.67°W., 54 lks. dist., with no marks visible. (Rec. N.65°W.)

At the corner point
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

T 31 S R 7 W
S 2 S 1
S 11 S 12
1969

from which new bearing trees:
A Fir 18" dia., bears N.65¼°E., 70 lks. dist., mkd. T31S R7W S1 BT.
A Fir 13" dia., bears S.36°E., 58 lks. dist. mkd. T31S R7W S12 BT.
A Fir 20" dia., bears S.26½°W., 64 lks. dist. mkd. T31S R7W S11 BT.
A Fir 23" dia., bears N.48¼°W., 26½ lks. dist. mkd. T31S R7W S2 BT.

Fd. and used by James Jelley in BLM Corrective Dependent Resurvey, under Group #680, surveyed June 1977 - (DCSO records, Vol. 41 Pages 16261-62)