

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1 & 2; 35 & 36, T30-7

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by W.H. Byars, Deputy Surveyor, under Contract #152, dated June 3, 1871, - (DCSO records Vol. 17 Page(s) 7229)

Set post corner to secs. 1, 2, 35 and 36, from which
An Alder 10" dia., bears N.60°E., 125 lks. dist.
An Alder 8" dia., bears S.55°E., 66 lks. dist.
A W.Oak 18" dia., bears S.30°W., 37 lks. dist.
A B.Oak 16" dia., bears N.55°W., 133 lks. dist.

BLM resurvey by James E. Jelley, Cadastral Surveyor, under Group #'s 350 and 680 - Surveyed April/Sept. 1969 - (DCSO records Vol. 35 Page(s) 14500)

Point for the sec. cor., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

T 30 S R 7 W
S 35 S 36
S 2 S 1
T 31 S
1969

from which

- A Fir 30" dia., bears N.14°E., 120 lks. dist. mkd. T30S R7W S36 BT.
- A Cedar 12" dia., bears S.12°E., 32½ lks. dist. mkd. T31S R7W S1 BT.
- A Fir 17" dia., bears S.76½°W., 52½ lks. dist. mkd. T31S R7W S2 BT.
- A Fir 20" dia., bears N.13 3/4°W., 82 lks. dist. mkd. T30S R7W S35 BT.

BLM resurvey by James E. Jelley, Cadastral Surveyor - under Group #680, surveyed June 1977 - (DCSO records Vol. 41 Page(s) 16259)

Point for the cor. of secs. 1, 2, 35 and 36, at proportionate distance; there is no remaining evidence of the original corner.

From this point, the cor. of secs. 1, 2, 35 and 36, erroneously reestablished by Jelley in 1969, bears N.65°11'W., 0.19 chs. dist., set, mkd. and witnessed as described in the official record.

I remove the iron post, destroy the marks on the bearing trees, and at the proportionate corner point Reset the iron post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd.

(Cont. Next Page)

TOWNSHIP 31 RANGE 07 POINT IDENTIFIER # 600700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1 & 2; 35 & 36, T30-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

T 30 S R 7 W
S 35 S 36
S 2 S 1
T 31 S
1977
1969

from which

- A Cedar 25" dia., bears N.24½°E., 75 lks. dist. mkd. T30S R7W S36 BT.
- A Cedar 18" dia., bears S.41°E., 59 lks. dist. mkd. T31S R7W S1 BT.
- A Cedar 7" dia., bears S.58½°W., 48½ lks. dist. mkd. T31S R7W S2 BT.
- A Cedar 11" dia., bears N.59¼°W., 71 lks. dist. mkd. T30S R7W S35 BT.

Fd. OK, June 1988 by H. Johnstone - M 106-52