

TOWNSHIP 31 RANGE 07 POINT IDENTIFIER # 640200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 25 and 36

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by W.H. Byars, Deputy Surveyor under contract # 448 dated June 13, 1882 (DCSO records Vol. 19 Page(s) 8037)

Set a Cedar post 3 ft. long, 3" sq., 18" in the ground for 1/4 sec. cor. marked 1/4 S. on N. face, from which
A Fir 20" dia., bears N.50°E., 48 lks. dist. mkd. 1/4 S BT
A Fir 24" dia., bears S.40°E., 8 lks. dist. mkd. 1/4 S BT.

Survey by Howard W. Johnstone - For: Roseburg Lumber Co. - May 28, 1962 - C.S. File 51/163-1

Found - 20" Fir N.5°E., now a snag, bark scribe visible.
24" Fir S.40°E., faint bark scribe.
Set 1" x 30" Iron pipe.
Scribed -22" D.Fir N.59°E., 42.8 ft.
Rescribed the orig. BT, S.40°E.

Douglas County Surveyors Office - R.B. Kimberling, M.W. Cline, crew - Oct. 20, 1977 - C.S. File 59/40-54

Found - A 1" Iron pipe, bears S.40°E., 1.1 ft. from corner set from OBT stump.
A 24" Fir stump bears S.40°E., 5.3 ft. with partially healed pitched over blaze. Lower bark scribe "BT" visible. (OBT used to set corner)
A 22" D.Fir stump bears N.58°E., 42.5 ft. (Rec. N.59°E., 42.8 ft. good to 1" I.P.) with well healed double blaze.
Set a 1" x 30" Iron pipe with brass cap, set 6" above ground, marked: Douglas County Surveyor
T 31 S R 7 W
1/4 S 25
S 36
1977
New BT - A 6" Chinkapin bears N.60°W., 85.4 ft. double blazed and scribed "1/4 S25 CS BT".
Corner is at SE. corner of a stand of timber. Road #31-7-25.1 is 400 ft. North.

Survey by Mark Smalley, L.S. #2354 - For: Kenneth Ford - July 1994 - M 120-43

Found - 1977 County BCIP & 1" IP.
22" Fir, N.59°E., 42.8', Part. healed.
24" Fir, S.40°E., 5.3', high stump.
New BTs -5" Fir, N.12°E., 18.1', "1/4 S BT"
7" Fir, S.70°E., 23.5', "1/4 S BT"
(Cont. Next Page)

TOWNSHIP 31 RANGE 07 POINT IDENTIFIER # 640200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 25 and 36

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

8" Pine, S.10°E., 19.2', "¼ S BT"
5" Fir, S.50°W., 23.3', "¼ S BT"