

TOWNSHIP 31 RANGE 07 POINT IDENTIFIER # 640300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 24 and 25

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GL0 survey by W.H. Byars, Deputy Surveyor under contract # 448 dated June 13, 1882 (DCSO records Vol. 19 Page(s) 8039)

-----  
Set Cedar post 3 ft. long, 3" sq., 18" in the ground for 1/4 sec. cor. marked 1/4 S. on N. face, from which  
A Fir 40" dia., bears N.26°E., 40 lks. dist. mkd. 1/4 S BT.  
A Fir 36" dia., bears S.20°W., 39 lks. dist. mkd. 1/4 S BT.

Douglas Co. Surveyors Office - James Byron, Deputy - Mike Darby; crew - May 31, 1963 - C.S. File 49/109-16

-----  
Found - Orig. 40" now 40" R.Fir, now 48" R.Fir, N.26°W., (Rec. N.E.)26.4 ft., no scribe marks found, face burned.

Orig. 38" now 44" R.Fir S.20°W., 25.7 ft., shows fair bark scribing "1/4 S".

Set brass cap at cor. mkd: County Surveyors office

T 31 S R 7 W

1/4 S 24

S 25

1963

New BTs -Rescribed now 44" Fir, S.22°W., 26.5 ft. "1/4 S25 CS BT"

20" R.Fir bears N.23°W., 48.6 ft. scribed "1/4 S24 CS BT"