

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 13 and 24

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 448 dated June 13, 1882 (DCSO records Vol. 19 Page(s) 8041)

Set Fir post 3 ft. long, 3" sq., 18" in the ground for ¼ sec. cor. marked ¼ S. on N. face, from which

A Cedar 30" dia., bears N.10°W., 36 lks. dist. mkd. ¼ S BT.

A Fir 12" dia., bears S.26°E., 28 lks. dist. mkd. ¼ S BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & Cliff Stone, crew - Dec. 1966 - C.S. File 54/36-20

Found - 12" now 20" D.Fir, S.26°E., 18.5 ft., opened for scribe "BT"

30" now 40" Cedar, N.10°W., 23.8 ft. (bearing should be N.10°E.)

3/4" Iron pipe at corner.

Set Brass cap at cor. mkd: County Surveyors Office

T 31 S R 7 W

¼ $\frac{S \ 13}{S \ 24}$

1966

New BT - 26" Fir S.21°W., 18.3 ft. mkd. ¼ S24 CS BT.

Best way to reach corner is from Cedar Camp, down ridge running NW. on old skid trail.

Douglas Co. Surveyors Office - Randall Smith, Stephen Flause, Sept. 10, 1996 - C.S. File 65/9-12

Found - 2½" dia. brass cap on a 1½" O.D. iron pipe protruding 12" above ground. (1966)

- 3/4" I.D. iron pipe, protrudes 2" above ground.

Found along north edge of BC/IP (source unknown)

Accessories Found -

30" now 40" dia. 4 ft. high Cedar stump with a previously opened blaze, scribing visible "S" bears N.10°E., 23.8 ft. (agrees with 1966 DCSO rec.) O.B.T.

12" now 24" dia. 4 ft. high D.Fir stump with a previously opened blaze, no scribing visible, bears S.29°E., 18.5 ft. (rec. S.26°E., 18.5 ft.) O.B.T.

26" now 26" dia. 4 ft. high D.Fir stump with a partially healed double blaze, scribing visible "1/4 S" bears S.21°W., 18.3 ft. (agrees with rec.) 1966

New Accessories -

6" dia. D.Fir, double blazed and scribed "¼ S24 CS BT" bears S.64°E., 37.1 ft.

5" dia. D.Fir, double blazed and scribed "¼ S13 CS BT" bears N.4°W., 26.9 ft. (Cont. Next Page)

