

TOWNSHIP 31 RANGE 07 POINT IDENTIFIER # 640600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 1 and 12

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 448 dated June 13, 1882 (DCSO records Vol. 19 Page(s) 8045)

Set a Fir post 40" long, 22" in the ground, 3" sq., marked $\frac{1}{4}$ S. on N. face for the $\frac{1}{4}$ sec. cor., from which
A Fir 22" dia., bears N.20°E., 40 lks. dist. mkd. $\frac{1}{4}$ S BT.
A Fir 7" dia., bears S.49°W., 37 lks. dist. mkd. $\frac{1}{4}$ S BT.

BLM resurvey by James E. Jelley, Cadastral Surveyor, under Group #'s 350 and 680 - Surveyed April/Sept. 1969 - (DCSO records Vol. 35 Page(s) 14505-06)

Point for the sec. cor., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd: $\frac{1}{4}$ $\frac{S 1}{S 12}$
T 31 S R 7 W
1969

from which

A Fir 30" dia., bears N.4°W., 74 lks. dist., mkd. $\frac{1}{4}$ S1 BT.
A Fir 5" dia., bears S.33 $\frac{1}{2}$ °E., 76 $\frac{1}{2}$ lks. dist. mkd. $\frac{1}{4}$ S12 BT.

Fd. OK, June 1988 by H. Johnstone - M 106-52