

TOWNSHIP 31 RANGE 07 POINT IDENTIFIER # 700200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 25 & 36; 30 & 31, T31-6

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - George W. Hyde under Contract #54 dated Feb. 19, 1855 (DCSO records Vol. 19 Page(s) 7945)

-----  
Set post cor. to secs. 25, 30, 31 and 36, on summit of NE. slope of ridge, from which

- A Fir 3" dia., bears N.49°E., 26 lks. dist.
- A Fir 20" dia., bears S.14°E., 15 lks. dist.
- A Fir 18" dia., bears S.75°W., 7 lks. dist.
- Chinquapin 6" dia., bears N.40°W., 53 lks. dist.

-----  
W.H. Byars, under contract # 448 survey dated June 13, 1882 (DCSO records Vol. 19 Page(s) 7951-52)

-----  
Set a Laurel post, 4 ft. long, 4" sq., 24" in the ground mkd. T31S R6W S30 on NE. face; S31 on E. face; S36 on the SW. face; and R7W S25 on NW. face; also one notch on S. and five notches on the North angles of the same for the corner to Secs. 25, 30, 31 and 36, from which

- A Laurel 6" dia., bears N.20°E., 11 lks. dist. mkd. T31S R6W S30 BT.
- A Laurel 12" dia., bears S.18°E., 82 lks. dist., mkd. T31S R6W S31 BT.
- A Laurel 5" dia., bears S.34°W., 40 lks. dist. mkd. T31S R7W S36 BT.
- A Laurel 6" dia., bears N.66°W., 32 lks. dist. mkd. T31S R7W S25 BT.

-----  
Survey by Howard Johnstone - For: Roseburg Lumber Co. - Jan. 4, 1961 - C.S. File 51/163-4

-----  
Found - 6" Madrone N.66°W., 31.1 ft., scribe visible.  
6" Madrone S.34°W., 26.4 ft., down.

Set 4" x 4" Cedar post.  
New BTs - 20" D.Fir S.57°W., 32.5 ft.  
8" D.Fir S.18°E., 24.0 ft.  
16" D.Fir N.46½°W., 57.0 ft.  
6" D.Fir N.78°E., 38.0 ft.

-----  
Douglas Co. Surveyors Office - John Powell, Frank Jones and Cliff Stone - Oct. 1966 - C.S. File 54/31-31

-----  
Found - 3/4" Iron pipe not recorded. (See M 33-49, Johnstone's survey)  
6" Madrone, now dead, N.66°W., 31.1 ft.  
20" now 22" D.Fir S.57°W., 32.5 ft., shows scribing  
8" now 10" D.Fir S.18°E., 24.0 ft. shows scribing.

(Cont. Next Page)

TOWNSHIP 31 RANGE 07 POINT IDENTIFIER # 700200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 25 & 36; 30 & 31, T31-6

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

16" now 18" D.Fir N.46½°W., 57.0 ft. shows scribing  
6" now 8" D.Fir N.78°E., 38.0 ft. shows scribing.  
Set Brass cap at cor. mkd: County Surveyors Office  
R7W T 31 S R6W  
S 25 | S 30  
S 36 | S 31  
1966

Survey by Howard Johnstone - For: Roseburg Lumber Co. - Feb.  
1969 - M 33-49

-----  
Found new BTs.  
Set 1" x 24" Iron pipe.