

TOWNSHIP 31 RANGE 07 POINT IDENTIFIER # 700240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 25; and 30 of T31-6

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - George W. Hyde under Contract #54 dated Feb. 19, 1855 (DCSO records Vol. 19 Page(s) 7945)

-----  
Set ¼ sec. post, from which  
A Fir 8" dia., bears N.89°E., 3 lks. dist.  
A Laurel 12" dia., bears S.52½°W., 8 lks. dist.

W.H. Byars, under contract # 448 survey dated June 13, 1882 (DCSO records Vol. 19 Page(s) 7952)

-----  
Find dim traces of old line, but no corners, Set a Laurel post, 3" sq., 40" long, 18" in the ground, mkd. ¼ S on W. side for the ¼ sec. cor. from which  
A Fir 14" dia., bears N.47°E., 6 lks. dist. mkd. ¼ S BT  
A Cedar 30" dia., bears S.42°W., 23 lks. dist. mkd. ¼ S BT.

Survey by Howard Johnstone - For: Roseburg Lumber Co. - May 28, 1962 - C.S. File 51/163-1

-----  
Found - Orig. bearing trees in good condition.  
Set 1" x 30" Iron pipe.

Douglas Co. Surveyors Office - Larry E. Monrean, Deputy - K. Cheney, P.L. Earle, crew - Jan. 3, 1977 - C.S. File 59/29-2

-----  
Found - ¾" x 24" I.P. at corner, firmly set.  
3" x 3" squared wooden post.  
Orig. 14" now 24" Fir bears N.48°E., 4.0 ft. (Rec. N.47°E.) Tree has bark scribing "¼ S BT."  
A 30" Cedar now 32" bears S.47°W., 15.2 ft. (Rec. S.42°W.) Tree has partially opened blaze, scribing visible "¼".  
Set 1" x 30" I.P. with brass cap attached at ¼ corner, cap stamped:

Douglas County Surveyor  
T 31 S  
R 1 R  
7 / 4 6  
W S25|S30 W  
1977

We place I.P. and wooden post beside brass cap. Cap is set in mound of stone.  
No new BTs necessary.

(Cont. Next Page)

TOWNSHIP 31 RANGE 07 POINT IDENTIFIER # 700240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 25; and 30 of T31-6

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Douglas County Surveyors Office - Randall Smith & Stephen  
Flause - Aug. 26, 1996 - C.S. 64/69-21

-----  
Mon. Fd.- 2½" Brass cap on a 1½" O.D. iron pipe protruding  
5" above a 2' dia. mound of stone. (1977  
DCS0)  
3/4" I.D. Iron pipe protrudes 7" above mound of  
stone along southwest edge of BC/IP. (1967  
Johnstone)  
Bt's Fd.- 24" dia. 5½' high D.Fir stump shows fragment bark  
scribing and a "B", bears N.48°E., 4'.  
36" dia. 1' high Cedar stump no blazes or  
scribing visible, bears S.47°W., 15.2'.  
New Bt's- 28" dia. D.Fir single blazed and scribed "¼ S25  
CS BT", bears N.73°W., 19.9'.  
28" dia. 1½' D.Fir stump with an 8" boat spike  
set through BT tag near top center of stump.  
B.S. is stamped "B02", B.S. bears S.48°W.,  
20.3'.  
30" dia. 2' high D.Fir stump with an 8" boat  
spike set through BT tag near top center of  
stump, B.S. is stamped "B01", B.S. bears  
S.73°E., 25.5'.