

TOWNSHIP 31 RANGE 07 POINT IDENTIFIER # 700340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for 24; & 19 of T31-6

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - George W. Hyde under Contract #54 dated Feb. 19, 1855 (DCSO records Vol. 19 Page(s) 7944-45)

Set ¼ sec. post, from which
A Fir 18" dia., bears S.82°W., 14 lks. dist.
A Laurel 8" dia., bears N .80°E., 11 lks. dist.

W.H. Byars, under contract # 448 survey dated June 13, 1882 (DCSO records Vol. 19 Page(s) 7953)

Set a cedar post 40" long, 4" sq., 20" in the ground, mkd. ¼S on W. side for the ¼ sec.cor., from which
A Laurel 16" dia., bears N.10°E., 26 lks. dist., mkd. ¼ S BT.
A Chinquapin 12" dia., bears N.25°W., 22 lks. dist., mkd. ¼ S BT.

Survey by Howard Johnstone - For Roseburg Lumber Co. - May 31, 1960 - M 18-66

Set ¼ corner - 1" x 24" Iron pipe.
15" D.Fir S.31°E., 25.1 ft.
7" D.Fir S.66°W., 29.2 ft.