

TOWNSHIP 31 RANGE 07 POINT IDENTIFIER # 700540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec 12; & 7 of T31-6

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - George W. Hyde under Contract #54 dated Feb. 19, 1855 (DCSO records Vol. 19 Page(s) 7943)

Set ¼ sec. post, from which
A Cedar 20" dia., bears S.48°W., 21 lks. dist.
A Laurel 10" dia., bears N.78°E., 13 lks. dist.

W.H. Byars, under contract # 448 survey dated June 13, 1882 (DCSO records Vol. 19 Page(s) 7955)

Set a Fir post, 3 ft. long, 3" sq., 20" in the ground, mkd. ¼ S on W. side for the ¼ sec. cor., from which
A Fir 10" dia., bears N.85°E., 22 lks. dist., mkd. ¼ S BT
A Fir 6" dia., bears S.80°W., 40 lks. dist., mkd. ¼ S BT.

BLM resurvey by James E. Jelley, under Group #'s 350 and 680, surveyed April/Sept. 1969 (DCSO records Vol. 35 Page(s) 14496)

Point for the ¼ sec. cor. of secs. 7 and 12, at proportionate distance; there is no remaining evidence of the original cor. Set an iron post, 28 ins. long, 2 1/2 ins. dia., 24 ins. in the ground, with brass cap marked ¼

S 12 S 7
R 7 W R 6 W
T 31 S
1969

from which
A Fir 9" dia., bears N.49°E., 49 lks. dist. mkd. ¼ S7 BT.
A Fir 8" dia., bears S.11°W., 56½ lks. dist., mkd. ¼ S12 BT.