

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1 & 12; 6 & 7, T31-6

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Original - George W. Hyde under Contract #54 dated Feb. 19, 1855 (DCSO records, Vol. 19 Page 7943)

-----  
Set post cor. for secs. 1, 6, 7 and 12, from which  
A Fir 12" dia., bears N.17°E., 118 lks. dist.  
A Fir 12" dia., bears N.42°W., 82 lks. dist.  
A Fir 18" dia., bears S.78°W., 109 lks. dist.  
(no other trees near)

-----  
GLO survey by W.H. Byars, under contract #448 dated June 13, 1882 (DCSO records Vol. 19 Page(s) 7955-56)

-----  
Set a Fir post, 4 ft. long, 4" sq., 24" in the ground, mkd. T31S R6W S6 on NE. face; S7 on SE. face; S12 on SW. face; R7W S1 on NW. face; also five notches on the S. and one notch on the N. angles of the same for the cor. to secs. 1, 6, 7 and 12, from which  
A Laurel 5" dia., N.85°E., 65 lks. mkd. T31S R6W S6 BT.  
A Fir 8" dia., bears S.54°E., 122 lks. dist. mkd. T31S R6W S7 BT.  
A Pine 5" dia., bears S.12°W., 25 lks. dist. mkd. T31S R7W S12 BT.  
A Fir 20" dia., bears N.65°W., 12 lks. dist., mkd. T31S R7W S1 BT.

Old cor. North 2.15 chs. Destroyed same.

-----  
BLM resurvey by James E. Jelley, under Group #'s 350 and 680, surveyed April/Sept. 1969 (DCSO records Vol. 35 Page(s) 14496-97)

-----  
Point for the cor. of secs. 1, 6, 7, and 12, at proportionate distance; there is no remaining evidence of the original cor. Set an iron post, 28 ins. long, 2 1/2 ins. dia., 24 ins. in the ground, with brass cap marked  
T 31 S  
R 7 W R 6 W  
S 1 S 6  
S 12 S 7  
1969

from which  
A Fir 5" dia., bears N.34½°E., 61 lks. dist., mkd. T31S R6W S6 BT.  
A Fir 14" dia., bears S.83½°E., 55½ lks. dist., mkd. T31S R6W S7 BT.  
A Fir 25" dia., bears S.24°W., 98 lks. dist., mkd. T31S R7W S12 BT.  
A Madrone 8" dia., bears N.49°W., 106 lks. dist., mkd. T31S R7W S1 BT.

---