

TOWNSHIP 31 RANGE 07 POINT IDENTIFIER # 700640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 1; & 6 of T31-6

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

Original - George W. Hyde under Contract #54 dated Feb. 19, 1855 (DCSO records, Vol. 19 Page 7943)

Set ¼ sec. post in dry rocky ravine, from which
A Laurel 6" dia., bears N.57°E., 131 lks. dist.
A Live Oak 4" dia., bears S.22°W., 52 lks. dist.

W.H. Byars, under contract # 448 survey dated June 13, 1882 (DCSO records Vol. 19 Page(s) 7956)

Set a stone 16x14x12, 10" in the ground, mkd. ¼ on W. side for the ¼ sec. cor., from which
A Laurel 8" dia., bears N.78°E., 72 lks. mkd. ¼ S BT.
A Laurel 5" dia., bears S.50°W., 100 lks. mkd. ¼ S BT.
Old cor. 2.10 chs. North. Destroyed same.

BLM resurvey by James E. Jelley, under Group #'s 350 and 680, surveyed Apr/Sept. 1969 (DCSO records Vol. 35 Page(s) 14497)

Point for the ¼ sec. cor. of secs. 1 and 6, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. dia., 24 ins. in the ground, with brass cap marked

¼
S 1 S 6
R 7 W R 6 W
T 31 S
1969

from which

A Fir 32" dia., bears S.88°E., 75½ lks. dist., mkd. ¼ S6 BT.

A Madrone 8" dia., bears N.55 3/4°W., 86 lks. dist., mkd. ¼ S1 BT.

Fd. OK, Howard Johnstone, June, 1988, M 106-52