TOWNSHIP 31 RANGE 08 POINT IDENTIFIER # 140400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 18 & 19

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars under contract #456, dated July 28, 1882 - (DCSO records Vol. 19 Page(s) 8158)

Set a fir post 3 ft. long, 3" sq., 18" in the ground, marked ¼ S for the ¼ sec. cor., from which
A fir, 15" dia., bears N.21°W., 14 lks., mkd: ¼ S BT.
A fir, 10" dia., bears S.46°E., 16 lks., mkd: ¼ S BT.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & C. Stone - Jan. 1967 - C.S. File 54/36-58

Found - 15" D.Fir, now 30", N.21°E. 9.2 ft. faint bark scribe, "S" BT". Distance from approx. face.
No trace of SE BT.
Set - Brass Cap at Cor. mkd: County Surveyors Office 1967 T31S R8W ¼ S 18 / S 19
New BTs- 14" D.Fir N.89°W. 7.0 ft. mkd. ¼ S18 CS BT.
30" D.Fir S.44½°E. 25.3 ft. mkd. ¼ S19 CS BT.

Fd. BC & 3 BTs by C. Woodruff, 4/2008 - M156-5

Ron Quimby - Crew: N. Fromdahl, J Leonard & R. Olsen - 2/2015 - C.S. File 65/87-15

Found - DCSO brass cap
36" D.Fir N.21°W., 9.2 (to face) good scar rec. N.21°E.
18" D.Fir N.89°W., 7.0 ft. good scar.
35" D.Fir S.44°E., 25.3 ft. good scar.
New - 12" W.Fir N.48°E., 16.3 ft. ¼ S18 BT.
Compass decl. 15½°E.