

TOWNSHIP 31 RANGE 08 POINT IDENTIFIER # 140500

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 7 & 18

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars under contract #456, dated July 28, 1882 - (DCSO records Vol. 19 Page(s) 8161)

Set a cedar post 3 ft. long, 3" sq. 18" in the ground, marked ¼ S for the ¼ sec. cor., from which

A fir, 12" dia., bears S.59°E., 9 lks., mkd: ¼ S BT.

A fir, 22" dia., bears N.26°W., 5 lks., mkd: ¼ S BT.

BLM dependent resurvey by C. Albert White, Harold D. Corbin, Cadastral Surveyors and Donald R. Beck, Survey Technician, under Group #350, surveyed Nov. 1960/Sept. 1962 - (DCSO records Vol. 32 Page(s) 13212)

The ¼ sec. cor. of secs. 7 & 8, determined at record bearing & distance from the orig. NW BT:

A fir, 40" dia., bears N.26°W., 5 lks., mkd: ¼ S BT.

Remarked ¼ S7 BT.

At the corner point

Set an iron post, 28" long, 2½" dia., 22" in the ground, with brass cap marked:

¼ $\frac{S \ 7}{S \ 18}$
T31S R8W
1962

from which a new BT

A fir, 32" dia., bears S.59½°E., 23 lks., mkd: ¼ S18 BT.

Corey Woodruff - 4/2008 - M156-5

Found - 1962 BLM BCIP
32" D.Fir stump bears S.58°E., 15.2'

New BTs- 7" D.Fir bears N.78°W., 8.0'

8" D.Fir bears N.17°E., 11.6'

8" D.Fir bears S.51°W., 9.0'

Note - BTs mkd were scribed tagged & painted unless otherwise noted. Distances were measured to a nail near the base of the tree at side center.