

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 6 & 7

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

GLO survey by W.H. Byars under contract #456, dated July 28, 1882 - (DCSO records Vol. 19 Page(s) 8164)

Set a stone 18x12x10", 8" in the ground, marked ¼ on N side for the ¼ sec. cor., and from which

A fir, 26" dia., bears N.12°E., 58 lks., mkd: ¼ S BT.

A fir, 72" dia., bears S.10°W., 38 lks., mkd: ¼ S BT.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - 3/7/1968 - C.S. File 54/36-36

Found - Stone mkd "¼", also unrecorded ¾" I.Pipe. 26", now 48" D.Fir, N.12°E. 38.3 ft., tree partly opened, no scribe visible, starting to show burl. 72" D.Fir, now 7.0, S.10°W., 25.1 ft., bark scribe visible.

Set - Brass Cap at Cor. mkd: County Surveyors T31S R8W
Office 1968 ¼ S 6
S 7

New BTs- 8" W.Fir S.75°W. 23.3 ft. mkd. ¼ S7 CS BT.
6" W.Fir N.9°E. 9.1 ft. mkd. ¼ S6 CS BT.

BLM dependent resurvey by Charles E. Akin, Jr., Cadastral Surveyor, under Group No. 819, surveyed Aug./Oct. 1972 - (DCSO Records Vol. 36 Page(s) 14936)

The ¼ sec. cor. of secs. 6 & 7, perpetuated and recorded by Powell, in 1968, monumented with iron pipe, 1" dia., firmly set, protruding 10" above ground with the original basalt stone alongside, 18x12x10", firmly set, 10" in the ground, mkd. ¼ on N. face, with brass cap (properly) mkd. from which the remains of the original bearing trees

A fir, 50" dia., bears N.12°E., 58 lks., with no marks visible on opened blaze.

A fir stump, 75" dia., bears S.10°W., 38 lks., with fragmentary scribe marks visible on bark blaze.

and bearing trees marked by Powell

A W.Fir, 8" dia., bears N.09°W., 14 lks., with fragmentary scribe marks visible on partially healed blaze.

A W.Fir, 10" dia. bears S.75°W., 35 lks. with fragmentary scribe marks visible on partially healed blaze.