

TOWNSHIP 31 RANGE 08 POINT IDENTIFIER # 140700

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 6; and 31, T30-8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 456 dated July 28, 1882 (DCSO records Vol. 17 Page(s) 7307-8)

Set a Fir post four ft. long, 4" sq., in the ground for the 1/4 sec. cor. mkd. 1/4 S on the N. side, and from which
A Fir 40" dia., bears S.32°E., 22 lks. dist. mkd. 1/4 S BT.
A Fir 16" dia., bears N.63°W., 29 lks. dist. mkd. 1/4 S BT.

BLM resurvey by C. Albert White; Harold D. Corbin, Cadastral Surveyors and Donald R. Beck, Surveying Technician, under Group #446, Surveyed Nov. 1960/Sept. 1962 - (DCSO records, Vol. 31 Page(s) 13190)

Point for the 1/4 sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28" long, 2 1/2" dia., 22" in the ground, with brass cap mkd:
T 30 S R 8 W
1/4 S 31
S 6
T 31 S
1962

from which
A Cedar 35" dia., bears N.16°W., 49 lks. dist. mkd. 1/4 S31 BT.
A Fir 45" dia., bears South 7 lks. dist. mkd. 1/4 S6 BT.

Carl Sweeden - 11/24/2003 - C.S. File 65/48-47

Found - 3 1/4" BC on 2 1/2" pipe, flush, 1962 BLM, good condition.
36" I.Cedar N.16°W., 32.34 ft. bark scribe vis. tag.
48" D.Fir BT South 4.2 ft., bark scribe vis. tag.
(4.62) 1962 rec.
New - 14" W.Fir N.44°E., 15.2 ft. marked "S 1/4 S31 BT" tag.
17" R.Cedar N.77°W., 39.5 ft. "S 1/4 S31 BT" tag.