

TOWNSHIP 31 RANGE 08 POINT IDENTIFIER # 200200

PRIMARY CORNER DESCRIPTION Cor. Secs. 29, 30, 31, & 32

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by W.H. Byars under contract #456, dated July 28, 1882 - (DCSO records Vol. 19 Page(s) 8150-1)

-----  
Set a stone 14x12x10", 8" in the ground, marked with 5 notches on the E and 1 notch on the S angles of same, for the cor. to secs. 29, 30, 31, & 32, from which

A fir, 30" dia. bears N.30°E. 56 lks. mkd: T31S R8W S29 BT

A fir, 36" dia. bears S.50°E. 40 lks. mkd: T31S R8W S32 BT

A laurel, 12" dia., bears S.65°W., 44 lks., mkd: T31S R8W S31 BT.

A fir, 36" dia. bears N.73°W. 32 lks. mkd: T31S R8W S30 BT

Douglas Co. Surveyors Office - Frank Jones & C. Stone - Jan. 1967 - C.S. File 54/36-54

-----  
Found - Orig. 30", now 38" D.Fir, N.30°E. 29.6 ft., do not find scribe.

Orig. 36" D. Fir, now snag, S.50°E. 26.4 ft.

Orig. 12", now 20" Laurel, S.65°E. 29.0 ft., face is rotted out.

36", now 44" D.Fir, N.73°W. 21.1 ft., shows faint but definite bark scribe "S 8 S".

Set - Brass Cap at Cor. mkd: COUNTY SURVEYORS T31S R8W  
OFFICE S 30 | S 29  
1967 S 31 | S 32

New BTs- 6" D.Fir N.64°E. 21.9 ft. mkd. T31S R8W S29 CS BT.

16" D.Fir S.11½°W. 46.4 ft. mkd. T31S R8W S31 CS BT.

15" D.Fir S.17°E. 49.4 ft. mkd. T31S R8W S32 CS BT.

Rescribed -

44" D.Fir N.73°W. 21.1 ft. mkd. T31S R8W S30 CS BT.

Note - This corner lies 100 ft. west & 248 ft. N. of Hayes Creek.

Fd. Ok by D. Edwards, April 2004 - M144-32