

PRIMARY CORNER DESCRIPTION Cor. Secs. 19, 20, 29, & 30

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 456 dated July 28, 1882 (DCSO records Vol. 19 Page(s) 8153)

Set a stone 18x14x10", 8" in the ground marked with 5 notches on the East & 2 notches on the South angles of same, for the cor. to secs. 19, 20, 29, & 30, from which

- A fir, 18" dia. bears N.79°E. 34 lks. mkd: T31S R8W S20 BT
- A fir, 14" dia. bears S.16°E. 48 lks. mkd: T31S R8W S29 BT
- A fir, 15" dia. bears S.24°W. 21 lks. mkd: T31S R8W S30 BT
- A fir, 16" dia. bears N.66°W. 45 lks. mkd: T31S R8W S19 BT

BLM Resurvey by C. Albert White, Harold D. Corbin, Cadastral Surveyors and Donald R. Beck, Surveying Technician, Under Group #350 & 446, Surveyed Nov. 1960/Sept. 1962 - (DCSO records Vol. 31 Page(s) 13211-2)

The cor. of secs. 19, 20, 29, & 30, determined at record bearing & dist. from the remaining orig. BTs:

- A fir, 26" dia., bears S.16°E., 48 lks., with illegible scribe marks visible on bark blaze.
- A fir, 28" dia., bears S.24°W., 21 lks. with healed blaze.
- A fir, 26" dia., bears N.66°W., 45 lks. with healed blaze.

At the corner point
Set an iron post, 28" long, 2½" dia., 20" in the ground, and in a mound of stone, 2½ ft. base to top, with brass cap marked:

T31S	R8W
<u>S 19</u>	<u>S 20</u>
<u>S 30</u>	<u>S 29</u>
1960	

from which a new BT
A fir, 14" dia., bears N.51°E., 112 lks., mkd: T31S R8W S20 BT.

Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J. Flause - 3/31/2004 - C.S. File 67/6-11

Found - 1960 BLM brass cap/IP 5 ft. south & 2 ft. higher than old road 1½ ft. below ground.

- 14" now 28" dia., D.Fir bark scribing visible "BT" & other illegible marks bears S.16°E., 28.7 ft., (rec. S.16°E., 31.7 ft.) OBT
- 16" now 32" dia., D.Fir with a previously opened partially healed blaze, no scribing visible, bears N.66°W. 32.0 ft. (rec. N.66°W. 29.7 ft) OBT

No other OBTs found.

- 14" now 23" dia., D.Fir with a fully healed single blaze, bears N.51°E., 72.6 ft. (rec. N.51°E., 73.9 ft.) 1960

continued next page

