

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 19 & 20

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars under contract #456, dated July 28, 1882 - (DCSO records Vol. 19 Page(s) 8156)

Set a Fir post, 3 ft. long, 3" sq., 18" in the ground, marked 1/4 S on W side, for the 1/4 sec. cor., from which

A fir, 24" dia., bears S.55°E., 30 lks., mkd: 1/4 S BT.

A fir, 14" dia., bears N.68°W., 56 lks., mkd: 1/4 S BT.

BLM dependent resurvey by C. Albert White, Harold D. Corbin, Cadastral Surveyors and Donald R. Beck, Survey Technician, under Group #350, surveyed Nov. 1960/Sept. 1962 - (DCSO records Vol. 32 Page(s) 13212)

The sec. cor. of secs. 19 & 20, determined at record bearing and distance from the original bearing trees:

A fir, 36" dia., bears S.55°E., 30 lks., with scribe marks 1/4 S BT visible on bark blaze.

A fir, 22" dia., bears N.68°W., 56 lks., with scribe marks 1/4 S visible on bark blaze.

At the corner point

Set an iron post, 28", long, 2 1/2" dia., 22" in the ground, with brass cap mkd.

T31S R8W
1/4
S 19|S 20
1960

Fd. Ok by S.P. Ness #811 - Dec. 1981 - M89-65

Ron Quimby - Crew: N. Fromdahl & R. Olsen - June 2014 - C.S. File 65/82-47

Found - BLM brass cap (properly mkd)
44" Fir S.55°E., 20.0 ft. vis. bark scribe.
10" Fir S.3°E., 32.5 ft. good scar. (Rec. ?)
33" Fir N.68°W., 37.0 ft. vis. bark scribe.
New - A 11" Fir N.54°E., 29.1 ft. scribed 1/4 S20 BT.
Note - Compass decl. 15 1/2°E.