

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars under contract #456, dated July 28, 1882 - (DCSO records Vol. 19 Page(s) 8156)

Set a cedar post 4 ft. long, 4" sq., 20" in the ground, marked T31S R8W S17 on NE, S20 on SE, S19 on SW & S18 on NW. Also 5 notches on the E & 3 notches on the south angles of the same for the cor to secs 17, 18, 19, & 20, and from which

A fir, 22" dia. bears N.49°E. 87 lks. mkd: T31S R8W S17 BT
A fir, 14" dia. bears S.61°E. 14 lks. mkd: T31S R8W S20 BT
A fir, 36" dia. bears S.64°W. 30 lks. mkd: T31S R8W S19 BT
A dogwood, 6" dia., bears N.26°W., 13 lks., mkd: T31S R8W S18 BT.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & C. Stone - Jan. 1967 - C.S. File 54/36-57

Found - 22" now 38" D.Fir, N.49°E., 57.4 ft. **I find bearing to be N.39°E.**, bark scribed "T31S R8 BT"
14" now 24" D.Fir S.61°E., 9.2 ft. bark scribed "T31S R8W S20 BT" **I find this bearing to be S.67½°E.**
36" now 39" D.Fir S.64°W., 19.8 ft., faint scribe visible "BT" **I find this bearing to be S.57°W.**
6" Dogwood, now snag, N.26°W., 8.6 ft., opened for scribe "BT"

Renewed corner by using 1 bearing and 4 distances.
Set - Brass cap at cor. mkd: COUNTY SURVEYORS T31S R8W
OFFICE S 18 | S 17
1967 S 19 | S 20

New BTs- 12" Cedar N.2°W., 26.5 ft. mkd. T31S R8W S18 CS BT.
7" W.Fir N.34°E., 15.3 ft. mkd. T31S R8W S17 CS BT.
9" hemlock S.45½°W., 37.2 ft mkd T31S R8W S19 CS BT.

BLM dependent resurvey by Charles E. Akin, Jr., Cadastral Surveyor, under Group No. 819, surveyed Aug./Sept. 1972 - (DCSO Records Vol. 36 Page(s) 14932)

The cor. of secs. 17. 18. 19, & 20, perpetuated and recorded by Powell, in 1961, monumented with an iron post, 1" in dia., firmly set, protruding 10 ins, above ground, with brass cap (properly) mkd.
from which the remaining original bearing trees

A fir, 39" dia., bears N.49°E., 87 lks., with scribe marks T31S R8W BT visible on bark blaze.
A fir, 24" dia., bears S.66°E., 14 lks., with scribe marks T31S R8W S20 BT visible on bark blaze (Record, S.61°E.)
A fir, 36" dia., bears S.58°W., 30 lks., with scribe marks BT visible on bark blaze. (Record, S.64°W.) cont.

Alias	Description
Alias	Description
Alias	Description
Alias	Description

and bearing trees marked by Powell

A W.Fir, 8" dia., bears N.35°E., 23 lks., with scribe marks T31S R8W S17 BT visible on open blaze.

A hemlock, 8" dia. bears S.46°W., 56 lks with scribe marks T31S R8W S18 BT visible on open blaze.

A cedar, 10" dia., bears N.8°W., 40 lks., with scribe marks T31S R8W S18 BT visible on open blaze.

Howard Johnstone - For: Roseburg Resources - June 4, 1987 - C.S. 63/26-6

Found - 1967 County brass cap, pulled out of ground from logging.

38" D.Fir, N.39°E., 57.4 ft. OBT. Stump.

24" D.Fir, S.66°E., 9.2 ft. OBT. Shows scar. OK

39" D.Fir, S.58°W., 19.8 ft. OBT. Stump.

12" Cedar, N.8°W., 26.5 ft. Gone

7" W. fir, N.35°E., 15.3 ft. Gone

9" Hemlock, S.46°W., 37.8 ft. Gone

RESET - Brass cap at record distances from remaining BT and the stumps.

New BTs- 44" D.Fir stump, S.58°W., 20.6 ft. Alum, nail in top of stump. Scribed "BT" in vertical section of undercut.

5" Hemlock, N.18°E., 45.3 ft. scribed "T31S R8W S17 BT" with tag.

10" Hemlock, N.75°W., 85.7 ft. scribed "T31S R8W S18 BT" with tag.

6" Hemlock, S.32°E., 22.9 ft. scribed "T31S R8W S20 BT" with tag.

All timber around corner has been cut except in Sec. 20. Corner is on NW slope 400 ft. below access road #31-8-20.

Ron Quimby - Crew: N. Fromdahl, J Leonard & R. Olsen - 2/2015 - C.S. File 65/87-16

Condition report only

Found - DCSO brass cap

38" fir stump N.39°E., 57.4 ft.

26" (high stump) S.66°E., 9.2 ft.

44" (high stump) S.58°W., 20.6 ft.

7" hemlock N.18°E., 45.3 ft. vis. scribe

14" hemlock S.32°E., 25.9 ft. (rec. 22.9) (high stump)

14" hemlock N.75°W., 85.7 vis. scribes.